

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 Date of issue: 04/09/2015 Revision date: 04/09/2015 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

: Newman Red Clay Product name Product code : Not available

Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Building and construction work

Details of the supplier of the safety data sheet

Gladding, McBean 601 7th Street Lincoln, CA 95648 800-776-1133

Emergency telephone number

Emergency number : CHEMTREC 1 (800) 424-9300

SECTION 2: Hazards identification

Classification of the substance or mixture

GHS-US classification

Skin Irritation 2

Eye Irritation 2A

Carcinogenicity 1A

Specific Target Organ Toxicity - Repeated Exposure 1

Label elements 2.2.

GHS-US labelling

Hazard pictograms (GHS-US)





Signal word (GHS-US)

: Danger

Hazard statements (GHS-US)

Causes skin irritation. Causes serious eye irritation. May cause cancer. Causes damage to lungs through prolonged or repeated exposure.

Precautionary statements (GHS-US)

: Wash hands thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. If exposed or concerned: Get medical advice/attention. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Store locked up. Dispose of contents and container in accordance with all local, regional, national and international regulations.

Other hazards

No additional information available.

Unknown acute toxicity (GHS US)

4 percent of the mixture consists of ingredient(s) of unknown acute toxicity.

04/09/2015 EN (English) Page 1



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable.

3.2. Mixture

| Name | Product identifier | % | GHS-US classification |
|-------------------|---------------------|----------|--|
| Quartz | (CAS No) 14808-60-7 | 30 - 60 | Carc. 1A STOT RE 1 |
| Aluminum oxide | (CAS No) 1344-28-1 | 10 - 30 | Not classified |
| Iron oxide | (CAS No) 1309-37-1 | 1 - 5 | Not classified |
| Titanium dioxide | (CAS No) 13463-67-7 | ≤ 3 | Carc. 2 |
| Potassium oxide | (CAS No) 12136-45-7 | ≤ 2 | Skin Corr. 1B |
| Magnesium oxide | (CAS No) 1309-48-4 | ≤ 1 | Not classified |
| Manganese dioxide | (CAS No) 1313-13-9 | ≤1 | Ox. Sol. 3 Acute Tox. 4 (Oral) Acute Tox. 4 (Inhalation) |

^{*} The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : If breathing is diffi

: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.

breathing. Get medical advice/attention if you leef driwell.

First-aid measures after skin contact : In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.

First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to

do, remove contact lenses, if worn. If irritation persists, get medical attention.

First-aid measures after ingestion : If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : Dust may cause respiratory tract irritation.

Symptoms/injuries after skin contact : Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking

of the skin.

Symptoms/injuries after eye contact : Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and

tear production, with marked redness and swelling of the conjunctiva.

Symptoms/injuries after ingestion : May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : None known.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon.

5.3. Advice for firefighters

Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures


General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.2. Methods and material for containment and cleaning up

For containment : Contain spill, then place in a suitable container. Minimize dust generation. Do not flush to sewer

or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for cleaning up : Vacuum or sweep material and place in a disposal container. Provide ventilation.





Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

6.3. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Avoid contact with skin and eyes. Avoid generating and breathing dust. Good housekeeping is important to prevent accumulation of dust. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. The use of compressed air for cleaning clothing, equipment, etc, is not recommended. Use with adequate ventilation.

Hygiene measures

: Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Keep out of the reach of children. Keep container tightly closed. Avoid any dust buildup by frequent cleaning and suitable construction of the storage area.

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| Quartz (14808-60-7) | | |
|---------------------|-------------------|--|
| ACGIH | ACGIH TWA (mg/m³) | 0.025 mg/m³ (respirable fraction) |
| OSHA | OSHA TWA | (30)/(%SiO2 + 2) mg/m³ (total dust) (250)/(%SiO2 + 5) mppcf (respirable fraction) (10)/(%SiO2 + 2) mg/m³ (respirable fraction) |

| Aluminum oxide (1344-28-1) | | |
|----------------------------|------------------------|--|
| ACGIH | Not applicable | |
| OSHA | OSHA PEL (TWA) (mg/m³) | 15 mg/m³ (total dust) 5 mg/m³ (respirable fraction) |

| Iron oxide (1309-37-1) | | |
|------------------------|------------------------|---|
| ACGIH | ACGIH TWA (mg/m³) | 5 mg/m³ (respirable fraction) |
| OSHA | OSHA PEL (TWA) (mg/m³) | 10 mg/m³ (fume) 15 mg/m³ (total dust) 5 mg/m³ (respirable fraction) |

| Titanium dioxide (13463-67-7 | ⁽) | |
|------------------------------|------------------------|-----------------------|
| ACGIH | ACGIH TWA (mg/m³) | 10 mg/m³ |
| OSHA | OSHA PEL (TWA) (mg/m³) | 15 mg/m³ (total dust) |

| Potassium oxide (12136-45-7 | ⁽) |
|-----------------------------|----------------|
| ACGIH | Not applicable |
| OSHA | Not applicable |

| Magnesium oxide (1309-48-4 |) | |
|----------------------------|------------------------|------------------------------------|
| ACGIH | ACGIH TWA (mg/m³) | 10 mg/m³ (inhalable fraction) |
| OSHA | OSHA PEL (TWA) (mg/m³) | 15 mg/m³ (fume, total particulate) |

| Manganese dioxide (1313-13-9) | | |
|-------------------------------|------------------------|-----------------|
| ACGIH | ACGIH TWA (mg/m³) | 0.2 mg /m³ (Mn) |
| OSHA | OSHA PEL (TWA) (mg/m³) | 5 mg/m³ (Mn) |

8.2. Exposure controls

Appropriate engineering controls

: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits. Use wet methods, if appropriate, to reduce the generation of dust.

Hand protection : Wear chemically resistant protective gloves.

Eye protection : Wear eye protection.

Skin and body protection : Wear suitable protective clothing.

04/09/2015 EN (English) 3/1



Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection

must be based on known or anticipated exposure levels, the hazards of the product and the

safe working limits of the selected respirator.

Environmental exposure controls : Maintain levels below Community environmental protection thresholds.

Other information : Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully

before eating or smoking. Handle according to established industrial hygiene and safety practices.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Solid
Appearance : Granular /
Color Powder : Orange
Odor : Odorless

Odor threshold No data available No data available Ηq Melting point No data available Freezing point No data available Boiling point : No data available No data available Flash point Relative evaporation rate (butylacetate=1) No data available Flammability (solid, gas) : Not flammable Explosive limits No data available Explosive properties : No data available No data available Oxidising properties Vapor pressure No data available

Relative density : 2.6

Relative vapor density at 20 °C : No data available

Solubility : Insoluble.

Partition coefficient: n-octanol/water : No data available
Log Kow : No data available
Auto-ignition temperature : No data available
Decomposition temperature : No data available
Viscosity : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available

9.2. Other information

No additional information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under normal storage conditions.

10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.





Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity : Not classified.

| Newman Red Clay | |
|-----------------------------------|---|
| LD50 oral rat | > 2000 ml/kg |
| LD50 dermal rabbit | > 2000 mg/kg |
| LC50 inhalation rat | > 5 mg/l/4h |
| Aluminum oxide (1344-28-1) | |
| LD50 oral rat | > 5000 mg/kg |
| Iron oxide (1309-37-1) | |
| LD50 oral rat | > 10000 mg/kg |
| Titanium dioxide (13463-67-7) | |
| LD50 oral rat | > 10000 mg/kg |
| Magnesium oxide (1309-48-4) | |
| LD50 oral rat | > 5000 mg/kg |
| Manganese dioxide (1313-13-9) | |
| LD50 oral rat | > 3478 mg/kg |
| Skin corrosion/irritation | : Causes skin irritation. |
| Serious eye damage/irritation | : Causes serious eye irritation. |
| Respiratory or skin sensitisation | : Based on available data, the classification criteria are not met. |
| Germ cell mutagenicity | : Based on available data, the classification criteria are not met. |

| Quartz (14808-60-7) | |
|--|--|
| IARC group | 1 - Carcinogenic to humans |
| National Toxicology Program (NTP) Status | 2 - Known Human Carcinogens |
| Iron oxide (1309-37-1) | |
| IARC group | 3 - Not classifiable |
| Titanium dioxide (13463-67-7) | |
| IARC group | 2B - Possibly carcinogenic to humans |
| Papraduativa toxicity | . Passed an available data the algorification criteria are not mot |

| Reproductive toxicity | : Based on available data, the classification criteria are not met. |
|--|---|
| Specific target organ toxicity (single exposure) | : Based on available data, the classification criteria are not met. |

Specific target organ toxicity (repeated exposure) : Causes damage to lungs through prolonged or repeated exposure. Respirable crystalline silica in the form of quartz or cristobalite from occupational sources is listed by the International

Agency for Research on Cancer (IARC) and National Toxicology Program (NTP) as a lung carcinogen. Prolonged exposure to respirable crystalline silica has been known to cause silicosis, a lung disease, which may be disabling. While there may be a factor of individual susceptibility to a given exposure to respirable silica dust, the risk of contracting silicosis and the severity of the disease is clearly related to the amount of dust exposure and the length of time (usually years) of exposure.

Based on available data, the classification criteria are not met. Aspiration hazard

: May cause cancer.

Symptoms/injuries after inhalation : Dust may cause respiratory tract irritation.

Symptoms/injuries after skin contact : Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking

of the skin.

Symptoms/injuries after eye contact Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and

tear production, with marked redness and swelling of the conjunctiva.

Symptoms/injuries after ingestion : May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

SECTION 12: Ecological information


Toxicity 12.1.

Carcinogenicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

12.2. Persistence and degradability

| Newman Red Clay | |
|-------------------------------|------------------|
| Persistence and degradability | Not established. |
| | |





Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

12.3. Bioaccumulative potential

| Newman Red Clay | |
|---------------------------|------------------|
| Bioaccumulative potential | Not established. |

12.4. Mobility in soil

No additional information available.

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations

: This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT.

Not regulated for transport.

Additional information

Other information

: No supplementary information available.

Special transport precautions : Do not handle until all safety precautions have been read and understood.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

| Aluminum oxide (1344-28-1) | |
|--|-----------------------|
| Listed on United States SARA Section 313 | |
| SARA Section 313 - Emission Reporting | 1.0 % (fibrous forms) |

15.2. US State regulations

| Newman Red Clay | |
|----------------------------|---|
| State or local regulations | PROPOSITION 65 WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. |

SECTION 16: Other information

Date of issue : 04/09/2015
Other information : None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.



6/1

