

# White Lightning® BOLT™ Quick Dry Siliconized Acrylic Latex Caulk

## Physical Properties:

## BOLT™ Quick Dry Siliconized Acrylic Latex Caulk

<b>Type:</b>	Adhesive Caulk	<b>Application Temperature:</b>	Above 50°F
<b>Color:</b>	White	<b>Service Temperature:</b>	-30°F to 180°F
<b>Shelf Life:</b>	12 Months	<b>Odor:</b>	Low/None
<b>Flammability:</b>	N/A	<b>Shrinkage:</b>	Low/Moderate
<b>Flash Point:</b>	N/A	<b>Vehicle:</b>	Water
<b>Full Cure Time:</b>	5-7 Days	<b>Weight Solids:</b>	76.3%
<b>Tack Free Time:</b>	10 Minutes	<b>Weight/Gallon:</b>	12.6 lbs/gal

## Performance Data:

<b>Joint Movement Capability:</b>	Good	<b>Mildew Resistance:</b>	Good
<b>Joint Size:</b>	1/2" x 1/4" to 1/8" x 1/8"	<b>Linear Coverage:</b>	
<b>Freeze -Thaw Stability:</b>	Passes Through 5 Cycles	<b>10 oz Cartridge</b>	
<b>Clean-Up:</b>	Water	<b>1/8" Bead Application</b>	96.7 ft
<b>Flexibility:</b>	Good	<b>1/4" Bead Application</b>	24.2 ft
<b>Painting:</b>	Paintable Within 30 Minutes	<b>5.3 oz Squeeze Tube</b>	
<b>Water Resistance:</b>	Good	<b>1/8" Bead Application</b>	53.2 ft
		<b>1/4" Bead Application</b>	13.3 ft

## Product Description:

White Lightning® BOLT™ Quick Dry Siliconized Acrylic Latex Caulk is an easy- to-use interior/exterior caulk specially formulated to dry quickly and can be painted within 30 minutes of application.

## Basic Uses:

BOLT™ Quick Dry is used for filling joints and openings around doors, windows, baseboards, trim, siding and vents.

## Surface Preparation:

Latex or oil based paint may be applied within 30 minutes of application. Allow extra dry time during periods of high humidity or cool temperatures.

## Cautions:

Use only with adequate ventilation. Avoid contact with eyes and skin. Wash hands after using. Do not transfer to other containers for storage.

## Limitations:

For best results apply at temperatures above 50°F. Never use in butt joints, joints subject to heavy abrasion and wear, or those that are frequently under water. Do not apply when rain or moisture is expected.

## Specifications:

Exceeds ASTM Spec C-834.



**For more information please call or write:**

White Lightning® Products • 101 Prospect Ave. NW • Cleveland, OH 44115  
1-800-241-5295 Option 1 Customer Service • 1-800-241-5295 Option 2 Technical Service  
[www.wlcaulk.com](http://www.wlcaulk.com)