

Safety Data Sheet Startex Paint Thinner

Version 0.0

Revision Date: 12/18/2015

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Startex Paint Thinner

Recommended use of the chemical and restrictions on use

Recommended use : Thinner

Manufacturer or supplier's details

Company : Nexeo Solutions LLC - STARTEX™
Address : 3 Waterway Square Place Suite 1000
The Woodlands, TX. 77380
United States of America

Emergency telephone number:

Health North America: 1-855-NEXEO4U (1-855-639-3648)

Health International: 1-855-NEXEO4U (1-855-639-3648)

Transport North America: CHEMTREC (1-800-424-9300)

Additional Information: : Responsible Party: Product Safety Group
E-Mail: msds@nexeosolutions.com
SDS Requests: 1-855-429-2661
SDS Requests Fax: 1-281-500-2370
Website: www.nexeosolutions.com

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 3

Skin irritation : Category 2

Eye irritation : Category 2A

Carcinogenicity : Category 1B

Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

Aspiration hazard : Category 1

GHS Label element

Hazard pictograms :



Signal word : Danger



Safety Data Sheet Startex Paint Thinner

Version 0.0

Revision Date: 12/18/2015

- Hazard statements : H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H350 May cause cancer.
- Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ eye protection/ face protection.
P281 Use personal protective equipment as required.
Response:
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.
P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P331 Do NOT induce vomiting.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical



Safety Data Sheet Startex Paint Thinner

Version 0.0

Revision Date: 12/18/2015

or alcohol-resistant foam for extinction.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Potential Health Effects

Carcinogenicity:

IARC

Group 2B: Possibly carcinogenic to humans

100-41-4

**Ethylbenzene

91-20-3

**Naphthalene

ACGIH

Confirmed animal carcinogen with unknown relevance to humans

100-41-4

**Ethylbenzene

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

Reasonably anticipated to be a human carcinogen

91-20-3

**Naphthalene

Emergency Overview

Appearance	liquid
Colour	clear, colourless
Odour	mild, Characteristic
Hazard Summary	No information available.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

CAS-No.	Chemical Name	Concentration (%)
---------	---------------	-------------------



Safety Data Sheet Startex Paint Thinner

Version 0.0

Revision Date: 12/18/2015

64742-47-8 / 64742-88-7	Distillates (pet), hydrotreated light AND/OR Solvent naphtha (pet), med aliph.	70 - 90
8052-41-3	Stoddard solvent	20 - 30
1330-20-7	**Mixed Xylenes	1 - 5
95-63-6	**1,2,4-trimethylbenzene	1 - 5
111-84-2	**Nonane	1 - 5
100-41-4	**Ethylbenzene	0.1 - 1
91-20-3	**Naphthalene	0.1 - 1

Special Notes: : ** Other substances in the product which may present a health or environmental hazard.

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.
If unconscious place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing : Alcohol-resistant foam



Safety Data Sheet Startex Paint Thinner

Version 0.0

Revision Date: 12/18/2015

media	Carbon dioxide (CO ₂) Dry chemical
Unsuitable extinguishing media	: High volume water jet
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: No hazardous combustion products are known
Specific extinguishing methods	: Use a water spray to cool fully closed containers.
Further information	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for fire-fighting if necessary.

NFPA Flammable and Combustible Liquids Classification: Combustible Liquid Class II

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).



Safety Data Sheet Startex Paint Thinner

Version 0.0

Revision Date: 12/18/2015

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : No smoking.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

CAS-No.	Components	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
64742-47-8 / 64742-88-7	Distillates (pet), hydrotreated light AND/OR Solvent naphtha (pet), med aliph.	TWA	500 ppm 2,000 mg/m ³	OSHA Z-1
		TWA	200 mg/m ³ (total hydrocarbon vapor)	ACGIH
		TWA	400 ppm 1,600 mg/m ³	OSHA P0
8052-41-3	Stoddard solvent	TWA	100 ppm	ACGIH



Safety Data Sheet
Startex Paint Thinner

Version 0.0

Revision Date: 12/18/2015

		TWA	350 mg/m ³	NIOSH REL
		C	1,800 mg/m ³	NIOSH REL
		TWA	500 ppm 2,900 mg/m ³	OSHA Z-1
		TWA	100 ppm 525 mg/m ³	OSHA P0
1330-20-7	**Mixed Xylenes	TWA	100 ppm 435 mg/m ³	OSHA Z-1
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
		STEL	150 ppm 655 mg/m ³	OSHA P0
		TWA	100 ppm 435 mg/m ³	OSHA P0
95-63-6	**1,2,4-trimethylbenzene	TWA	25 ppm 125 mg/m ³	NIOSH REL
111-84-2	**Nonane	TWA	200 ppm	ACGIH
		TWA	200 ppm 1,050 mg/m ³	NIOSH REL
		TWA	200 ppm 1,050 mg/m ³	OSHA P0
100-41-4	**Ethylbenzene	TWA	20 ppm	ACGIH
		TWA	100 ppm 435 mg/m ³	NIOSH REL
		ST	125 ppm 545 mg/m ³	NIOSH REL
		TWA	100 ppm 435 mg/m ³	OSHA Z-1
		TWA	100 ppm 435 mg/m ³	OSHA P0
		STEL	125 ppm 545 mg/m ³	OSHA P0
91-20-3	**Naphthalene	TWA	10 ppm	ACGIH
		STEL	15 ppm	ACGIH
		TWA	10 ppm 50 mg/m ³	NIOSH REL
		ST	15 ppm 75 mg/m ³	NIOSH REL
		TWA	10 ppm 50 mg/m ³	OSHA Z-1
		TWA	10 ppm 50 mg/m ³	OSHA P0
		STEL	15 ppm 75 mg/m ³	OSHA P0

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis



Safety Data Sheet Startex Paint Thinner

Version 0.0

Revision Date: 12/18/2015

**Mixed Xylenes	1330-20-7	Methylhippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	1.5 g/g creatinine	ACGIH BEI
**Ethylbenzene	100-41-4	Sum of mandelic acid and phenyl glyoxylic acid	Urine	End of shift at end of work-week	0.7 g/g creatinine	ACGIH BEI

Personal protective equipment

- Respiratory protection : No personal respiratory protective equipment normally required.
In the case of vapour formation use a respirator with an approved filter.
- Hand protection
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.
- Skin and body protection : impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday,

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Colour : clear, colourless
- Odour : mild, Characteristic



Safety Data Sheet Startex Paint Thinner

Version 0.0

Revision Date: 12/18/2015

Odour Threshold	: No data available
pH	: No data available
Freezing Point	: No data available
Boiling Point (Boiling point/boiling range)	: 158 - 198 °C (316 - 388 °F)
Flash point	: 39.44 - 45 °C (102.99 - 113 °F)
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Burning rate	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Relative density	: 0.775 - 0.784 @ 20 °C (68 °F) Reference substance: (water = 1)
Density	: No data available
Bulk density	: No data available
Solubility(ies)	
Water solubility	: Negligible
Solubility in other sol- vents	: No data available
Partition coefficient: n- octanol/water	: No data available
Auto-ignition temperature	: 276 °C
Thermal decomposition	: No data available

SECTION 10. STABILITY AND REACTIVITY



Safety Data Sheet Startex Paint Thinner

Version 0.0

Revision Date: 12/18/2015

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air.
Conditions to avoid	: Keep away from heat, flame, sparks and other ignition sources.
Incompatible materials	: Oxidizing agents Peroxides Reducing agents Strong bases
Hazardous decomposition products	: Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute inhalation toxicity : Acute toxicity estimate : > 40 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Components:

64742-47-8 / 64742-88-7:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : LD50 (Rabbit, male and female): > 2,000 mg/kg
Method: Fixed dose procedure
GLP: yes
Assessment: The substance or mixture has no acute dermal toxicity

8052-41-3:

Acute oral toxicity : LD50 (Rat, male and female): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat, male and female): >5500
Exposure time: 4 h



Safety Data Sheet Startex Paint Thinner

Version 0.0

Revision Date: 12/18/2015

Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 3,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Product:

Result: Irritating to skin.

Components:

64742-47-8 / 64742-88-7:

Species: Rabbit
Exposure time: 24 h
Method: In vivo
Result: Irritating to skin.

8052-41-3:

Species: Rabbit
Exposure time: 24 h
Method: In vivo
Result: Mild skin irritation

Serious eye damage/eye irritation

Product:

Result: Irritating to eyes.

Components:

64742-47-8 / 64742-88-7:

Species: Rabbit
Result: Irritating to eyes.

8052-41-3:

Species: Rabbit
Result: Mild eye irritation
Method: In vivo

Respiratory or skin sensitisation

Components:

64742-47-8 / 64742-88-7:

Test Type: Buehler Test
Species: Guinea pig



Safety Data Sheet Startex Paint Thinner

Version 0.0

Revision Date: 12/18/2015

Method: In vivo
Result: Did not cause sensitisation on laboratory animals.
GLP: yes

8052-41-3:

Exposure routes: Dermal
Species: Guinea pig
Method: In vivo
Result: Did not cause sensitisation on laboratory animals.

Germ cell mutagenicity

Components:

64742-47-8 / 64742-88-7:

Germ cell mutagenicity- : Tests on bacterial or mammalian cell cultures did not
Assessment show mutagenic effects.

8052-41-3:

Germ cell mutagenicity- : Mutagenicity classification not possible from current
Assessment data

Carcinogenicity

Components:

64742-47-8 / 64742-88-7:

Carcinogenicity - As- : Not classifiable as a human carcinogen.
essment

8052-41-3:

Carcinogenicity - As- : Carcinogenicity classification not possible from current
essment data.

100-41-4:

Carcinogenicity - As- : Not classifiable as a human carcinogen.
essment

Reproductive toxicity

Components:

64742-47-8 / 64742-88-7:

Reproductive toxicity - : Animal testing did not show any effects on fertility.
Assessment Embryotoxicity classification not possible from current
data.

8052-41-3:

Reproductive toxicity - : Fertility classification not possible from current data.
Assessment Embryotoxicity classification not possible from current
data.



Safety Data Sheet Startex Paint Thinner

Version 0.0

Revision Date: 12/18/2015

STOT - single exposure

Product:No data available

Components:

64742-47-8 / 64742-88-7:

Exposure routes:	Target Organs:	Assessment:	Remarks:
Inhalation	Central nervous system	May cause drowsiness or dizziness., The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.	

8052-41-3:

Exposure routes:	Target Organs:	Assessment:	Remarks:
Inhalation	Central nervous system	May cause drowsiness or dizziness., The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.	

1330-20-7:No data available

95-63-6:No data available

111-84-2:No data available

100-41-4:No data available

91-20-3:No data available

STOT - repeated exposure

Product:No data available

Components:

64742-47-8 / 64742-88-7:No data available

8052-41-3:No data available



Safety Data Sheet Startex Paint Thinner

Version 0.0

Revision Date: 12/18/2015

1330-20-7:No data available

95-63-6:No data available

111-84-2:No data available

100-41-4:No data available

91-20-3:No data available

Repeated dose toxicity

Components:

64742-47-8 / 64742-88-7:

Species: Rat, male

LOAEL: 750 mg/kg

Application Route: Oral

Exposure time: 70 - 90 days

Number of exposures: daily

Dose: 0, 750, 1500, 3000 mg/kg/d

GLP: yes

Symptoms: weight loss, Liver effects, Stomach/intestinal disorders

Species: Rat, male and female

NOAEL: 24

Application Route: Inhalation

Test atmosphere: vapour

Exposure time: 4 wks

Number of exposures: 6 h/d, 5 d/wk

Dose: 0, 24 mg/m³

GLP: yes

Remarks: Information given is based on data obtained from similar substances.

8052-41-3:

Species: Rat, male and female

NOAEL: 275

Application Route: Inhalation

Exposure time: 14 wks

Number of exposures: 6 h/d, 5 d/wk

Dose: 138, 275, 550, 1100, 2200mg/m³

Group: yes

Symptoms: nasal symptoms, Testicular effects, Kidney disorders

Remarks: male rat hydrocarbon nephropathy not relevant to humans



Safety Data Sheet Startex Paint Thinner

Version 0.0

Revision Date: 12/18/2015

Species: Mouse, male and female
LOAEL: 138
Application Route: Inhalation
Exposure time: 14 wks
Number of exposures: 6 h/d, 5 d/wk
Dose: 138, 275, 550, 1100, 2200mg/m³
Group: yes
Symptoms: Spleen effects

Aspiration toxicity

Product:

May be fatal if swallowed and enters airways.

Components:

64742-47-8 / 64742-88-7:

May be fatal if swallowed and enters airways.

8052-41-3:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

64742-47-8 / 64742-88-7:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l
Exposure time: 96 h
Test Type: semi-static test
Analytical monitoring: yes
Method: OECD Test Guideline 203
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 1.4 mg/l
Exposure time: 48 h
Test Type: static test



Safety Data Sheet Startex Paint Thinner

Version 0.0

Revision Date: 12/18/2015

Analytical monitoring: yes
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae : EL50 (Pseudokirchneriella subcapitata (green algae)):
1 mg/l
End point: Growth rate
Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes
Method: OECD Test Guideline 201
GLP: yes

Ecotoxicology Assessment
Acute aquatic toxicity

: Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

8052-41-3:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : LL50 (Chaetogammarus marinus (Amphipod)): 3.5 mg/l
Exposure time: 96 h

Toxicity to algae : EbL50 (Pseudokirchneriella subcapitata (green algae)): 2.5 mg/l
End point: Biomass
Exposure time: 72 h

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Persistence and degradability

Components:

64742-47-8 / 64742-88-7:

Biodegradability : aerobic
Concentration: 101 mg/l
Biodegradation: 61 %
Exposure time: 28 d
GLP: yes
Remarks: Readily biodegradable

8052-41-3:

Biodegradability : Remarks: No data available



Safety Data Sheet Startex Paint Thinner

Version 0.0

Revision Date: 12/18/2015

Bioaccumulative potential

Components:

1330-20-7:

Partition coefficient: n-octanol/water : log Pow: 2.77 - 3.15

95-63-6:

Partition coefficient: n-octanol/water : Remarks: No data available

91-20-3:

Partition coefficient: n-octanol/water : log Pow: 3.4 (25 °C)
pH: 7 - 7.5

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation

40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues

: Dispose of in accordance with all applicable local, state and federal regulations.
For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact NEXEO's Environmental Services Group at 800-637-7922.

Contaminated packaging

: Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty



Safety Data Sheet

Startex Paint Thinner

Version 0.0

Revision Date: 12/18/2015

drum.

SECTION 14. TRANSPORT INFORMATION

IATA (International Air Transport Association): UN1263, PAINT RELATED MATERIAL, 3, III, Flash Point: 39.44 - 45 °C (102.99 - 113 °F)

IMDG (International Maritime Dangerous Goods): UN1263, PAINT RELATED MATERIAL, 3, III, Marine Pollutant (PETROLEUM DISTILLATE, HYDROTREATED LIGHT, STODDARD SOLVENT)

DOT (Department of Transportation): UN1263, PAINT RELATED MATERIAL, 3, III

Special Notes: : The flash point for this material is greater than 100 F (38 C). Therefore, in accordance with 49 CFR 173.150(f) non-bulk containers (<450L or <119 gallon capacity) of this material may be shipped as non-regulated when transported solely by land, as long as the material is not a hazardous waste, a marine pollutant, or specifically listed as a hazardous substance.

SECTION 15. REGULATORY INFORMATION

OSHA Hazards : Combustible Liquid, Carcinogen, Moderate skin irritant, Moderate eye irritant, Moderate respiratory irritant, Specific target organ toxicity - single exposure, Aspiration hazard

WHMIS Classification : B3: Combustible Liquid
D2A: Very Toxic Material Causing Other Toxic Effects
D2B: Toxic Material Causing Other Toxic Effects

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
**Mixed Xylenes	1330-20-7	100	2505

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Fire Hazard
Chronic (Delayed) Health Hazard
Immediate (Acute) Health Hazard



Safety Data Sheet Startex Paint Thinner

Version 0.0

Revision Date: 12/18/2015

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

1330-20-7	**Mixed Xylenes	3.9925 %
95-63-6	**1,2,4-trimethylbenzene	1.0075 %
100-41-4	**Ethylbenzene	0.1798 %
91-20-3	**Naphthalene	0.1798 %

Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

1330-20-7	**Mixed Xylenes	3.9925 %
100-41-4	**Ethylbenzene	0.1797 %
91-20-3	**Naphthalene	0.1797 %
98-82-8	**Cumene	0.079 %
108-88-3	**Toluene	0.079 %
71-43-2	**Benzene	0.079 %

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

1330-20-7	**Mixed Xylenes	3.9925 %
100-41-4	**Ethylbenzene	0.1798 %
91-20-3	**Naphthalene	0.1798 %
98-82-8	**Cumene	0.079 %
108-88-3	**Toluene	0.079 %
71-43-2	**Benzene	0.079 %

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

1330-20-7	**Mixed Xylenes	3.9925 %
100-41-4	**Ethylbenzene	0.1798 %
98-82-8	**Cumene	0.079 %
108-88-3	**Toluene	0.079 %
71-43-2	**Benzene	0.079 %

Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

1330-20-7	**Mixed Xylenes	3.9925 %
100-41-4	**Ethylbenzene	0.1798 %
91-20-3	**Naphthalene	0.1798 %
108-88-3	**Toluene	0.079 %
71-43-2	**Benzene	0.079 %



Safety Data Sheet Startex Paint Thinner

Version 0.0

Revision Date: 12/18/2015

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

1330-20-7	**Mixed Xylenes	3.9925 %
100-41-4	**Ethylbenzene	0.1798 %
91-20-3	**Naphthalene	0.1798 %
108-88-3	**Toluene	0.079 %
71-43-2	**Benzene	0.079 %

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

US State Regulations

Massachusetts Right To Know

8052-41-3	Stoddard solvent	20 - 30 %
1330-20-7	**Mixed Xylenes	1 - 5 %
95-63-6	**1,2,4-trimethylbenzene	1 - 5 %
111-84-2	**Nonane	1 - 5 %
71-43-2	**Benzene	0 - 0.1 %

Pennsylvania Right To Know

64742-47-8 / 64742-88-7	Distillates (pet), hydrotreated light AND/OR Solvent naphtha (pet), med aliph.	70 - 90 %
8052-41-3	Stoddard solvent	20 - 30 %
1330-20-7	**Mixed Xylenes	1 - 5 %
95-63-6	**1,2,4-trimethylbenzene	1 - 5 %
111-84-2	**Nonane	1 - 5 %
100-41-4	**Ethylbenzene	0.1 - 1 %
91-20-3	**Naphthalene	0.1 - 1 %
98-82-8	**Cumene	0 - 0.1 %
108-88-3	**Toluene	0 - 0.1 %
71-43-2	**Benzene	0 - 0.1 %

New Jersey Right To Know

64742-47-8 / 64742-88-7	Distillates (pet), hydrotreated light AND/OR Solvent naphtha (pet), med aliph.	70 - 90 %
8052-41-3	Stoddard solvent	20 - 30 %
1330-20-7	**Mixed Xylenes	1 - 5 %
95-63-6	**1,2,4-trimethylbenzene	1 - 5 %
111-84-2	**Nonane	1 - 5 %
100-41-4	**Ethylbenzene	0.1 - 1 %
91-20-3	**Naphthalene	0.1 - 1 %

California Prop 65

	WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.
108-88-3	**Toluene



Safety Data Sheet Startex Paint Thinner

Version 0.0

Revision Date: 12/18/2015

71-43-2 **Benzene
WARNING! This product contains a chemical known to
the State of California to cause cancer.
100-41-4 **Ethylbenzene
91-20-3 **Naphthalene
98-82-8 **Cumene
71-43-2 **Benzene

The components of this product are reported in the following inventories:

United States TSCA Inventory	:	y (positive listing) (On TSCA Inventory)
Canadian Domestic Substances List (DSL)	:	y (positive listing) (All components of this product are on the Canadian DSL.)
Australia Inventory of Chemical Substances (AICS)	:	y (positive listing) (On the inventory, or in compliance with the inventory)
Korea. Korean Existing Chemicals Inventory (KECI)	:	y (positive listing) (On the inventory, or in compliance with the inventory)
Philippines Inventory of Chemicals and Chemical Substances (PICCS)	:	y (positive listing) (On the inventory, or in compliance with the inventory)
China. Inventory of Existing Chemical Substances in China (IECSC)	:	y (positive listing) (On the inventory, or in compliance with the inventory)
Switzerland. New notified substances and declared preparations	:	y (positive listing) (The formulation contains substances listed on the Swiss Inventory)



Safety Data Sheet


Startex Paint Thinner

Version 0.0

Revision Date: 12/18/2015

SECTION 16. OTHER INFORMATION **Further information**

NFPA:



HMIS III:

HEALTH	2*
FLAMMABILITY	2
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
 2 = Moderate, 3 = High
 4 = Extreme, * = Chronic

The information accumulated is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made become available subsequently to the date hereof, we do not assume any responsibility for the results of its use. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by NEXEO™ Solutions EHS Product Safety Department (1-855-429-2661) MSDS@nexeosolutions.com.

Material number:

16067564, 16067563, 16067562, 16067561, 16067560, 16067559, 16067558, 16067557, 16056402, 16056401, 16056400, 16056399, 16056398, 16056397, 16056396, 16056395, 16056394

Key or legend to abbreviations and acronyms used in the safety data sheet

ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration



Safety Data Sheet Startex Paint Thinner

Version 0.0

Revision Date: 12/18/2015

EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS >=	Globally Harmonized System Greater Than or Equal To	RCRA STEL	Resource Conservation Recovery Act Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50			Lethal Concentration 50%