



SAFETY DATA SHEET

Issuing Date 09-Apr-2014

Revision Date 19-Feb-2015

Revision Number 3

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

GHS product identifier

Product Name Dykem Transparent Stain Aerosol - Steel Blue and Steel Red

Other means of identification

Part Number Dk Blue - Steel Blue (80000), Red - Steel Red (80096)

Formula Code Dk Blue - Steel Blue (8703A), Red - Steel Red (8704A)

UN-Number UN1950

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Staining Colors

Uses advised against No information available

Supplier's details

Supplier Address

ITW PRO BRANDS
805 E. Old 56 Highway
Olathe, KS 66061
TEL: 1-800-443-9536

Emergency telephone number

Emergency Telephone Number 800-535-5053 Infotrac

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200)

Serious Eye Damage/Eye Irritation	Category 1
Reproductive Toxicity	Category 2
Specific Target Organ Systemic Toxicity (Single Exposure)	Category 3
Flammable aerosols	Category 1
Gases under pressure	Compressed gas

GHS Label elements, including precautionary statements**Emergency Overview****Signal Word****Danger****Hazard Statements**

- Causes mild skin irritation
- Causes serious eye damage
- Suspected of damaging fertility or the unborn child
- May cause respiratory irritation
- May cause drowsiness or dizziness
-
- Extremely flammable aerosol
- Contains gas under pressure; may explode if heated

**Appearance** Red, Blue, Color: Thin viscosity, (for liquid)**Physical State** Aerosol.**Odor** Sweet, Solvent**Precautionary Statements****Prevention**

- Wear eye/face protection.
- Avoid breathing dust/fume/gas/mist/vapors/spray.
- Use only outdoors or in a well-ventilated area.
- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Use personal protective equipment as required.
- Keep away from heat/sparks/open flames/hot surfaces - No smoking.
- Do not spray on an open flame or other ignition source
- Pressurized container: Do not pierce or burn, even after use.

General Advice

- If exposed or concerned: Get medical attention/advice

Eyes

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- Immediately call a POISON CENTER or doctor/physician.

Inhalation

- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Storage

- Store in a well-ventilated place. Keep container tightly closed.
- Store locked up.
- Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
- Protect from sunlight

Disposal

- Dispose of contents/container to an approved waste disposal plant.

Hazard Not Otherwise Classified (HNOC)

Not applicable

Other information**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS-No	Weight %	Trade secret
Ethanol	64-17-5	15-40	*
n-Butyl acetate	123-86-4	10-30	*
Butane	106-97-8	7-13	*
n-Butyl alcohol	71-36-3	5-10	*
Diacetone alcohol	123-42-2	1-5	*
Nitrocellulose	9004-70-0	1-5	*
Isopropyl alcohol	67-63-0	1-5	*
n-Propyl acetate	109-60-4	1-5	*
Basic green 4	18015-76-4	0.1-1	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES**Description of necessary first-aid measures**

General Advice	Immediate medical attention is required. Show this safety data sheet to the doctor in attendance. If symptoms persist, call a physician.
Eye Contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.
Skin Contact	Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
Inhalation	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If symptoms persist, call a physician.
Ingestion	Rinse mouth. Drink plenty of water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Consult a physician if necessary
Protection of First-aiders	Use personal protective equipment. Remove all sources of ignition.

Most important symptoms/effects, acute and delayed

Most Important Symptoms/Effects No information available.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES**Suitable Extinguishing Media**

Carbon dioxide (CO₂). Foam. Dry chemical. Water fog.

Unsuitable Extinguishing Media None

Specific Hazards Arising from the Chemical

Flammable. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapors may travel to source of ignition and flash back. Ruptured cylinders may rocket.

Explosion Data**Sensitivity to Mechanical Impact**

None.

Sensitivity to Static Discharge

Yes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use water spray to cool surrounding containers.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures**Personal Precautions**

Ensure adequate ventilation.

Environmental Precautions**Environmental Precautions**

See Section 12 for additional Ecological Information.

Methods and materials for containment and cleaning up**Methods for Containment**

Prevent further leakage or spillage if safe to do so.

Methods for Cleaning Up

Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling**Handling**

Handle in accordance with good industrial hygiene and safety practice.

Conditions for safe storage, including any incompatibilities**Storage**

Keep containers tightly closed in a dry, cool and well-ventilated place.

Incompatible Products

Strong oxidizing agents. Strong acids. Strong reducing agents. Strong alkalis.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Ethanol 64-17-5	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1900 mg/m ³	IDLH: 3300 ppm 10% LEL TWA: 1000 ppm TWA: 1900 mg/m ³
n-Butyl acetate 123-86-4	STEL: 200 ppm TWA: 150 ppm	TWA: 150 ppm TWA: 710 mg/m ³ (vacated) TWA: 150 ppm (vacated) TWA: 710 mg/m ³ (vacated) STEL: 200 ppm (vacated) STEL: 950 mg/m ³	IDLH: 1700 ppm TWA: 150 ppm TWA: 710 mg/m ³ STEL: 200 ppm STEL: 950 mg/m ³
Butane 106-97-8	STEL: 1000 ppm	(vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m ³	TWA: 800 ppm TWA: 1900 mg/m ³
Propane 74-98-6	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m ³	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³

n-Butyl alcohol 71-36-3	TWA: 20 ppm	TWA: 100 ppm TWA: 300 mg/m ³ (vacated) S* (vacated) Ceiling: 50 ppm (vacated) Ceiling: 150 mg/m ³	IDLH: 1400 ppm Ceiling: 50 ppm Ceiling: 150 mg/m ³
Diacetone alcohol 123-42-2	TWA: 50 ppm	TWA: 50 ppm TWA: 240 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 240 mg/m ³	IDLH: 1800 ppm TWA: 50 ppm TWA: 240 mg/m ³
Isopropyl alcohol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m ³	IDLH: 2000 ppm 10% LEL TWA: 980 mg/m ³ TWA: 400 ppm STEL: 500 ppm STEL: 1225 mg/m ³
n-Propyl acetate 109-60-4	STEL: 250 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 840 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 840 mg/m ³ (vacated) STEL: 250 ppm (vacated) STEL: 1050 mg/m ³	IDLH: 1700 ppm TWA: 200 ppm TWA: 840 mg/m ³ STEL: 250 ppm STEL: 1050 mg/m ³

Immediately Dangerous to Life or Health. ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH:

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls**Engineering Measures**

Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment**Eye/Face Protection**

No special protective equipment required. Avoid contact with eyes. Risk of contact, wear: Chemical splash goggles.

Skin and Body Protection

Chemical resistant gloves.

Respiratory Protection

None required under normal usage. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn.

Hygiene Measures

When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Aerosol	Appearance	Red Blue, Color: Thin viscosity, (for liquid)
Odor	Sweet, Solvent	Odor Threshold	No information available
<u>Property</u>	<u>Values</u>	<u>Remarks/ - Method</u>	
pH	No data available	None known	
Melting Point/Range	No data available	None known	
Boiling Point/Boiling Range	76.667-125 °C / 170-257 °F	None known	
Flash Point	11.667 °C / 53 °F	None known	
Evaporation rate	< 1 (BuAc = 1)	BuAc = 1	
Flammability (solid, gas)	No data available	None known	
Flammability Limits in Air			
upper flammability limit	No data available 19.0		
lower flammability limit	No data available 1.40		
Vapor Pressure	No data available	None known	
Vapor Density	> 1 (air = 1)	None known	
Specific Gravity	No data available.	None known	

Water Solubility	Negligible	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	No data available	None known
Autoignition Temperature	No data available	None known
Decomposition Temperature	No data available	None known
Viscosity	No data available	None known

Flammable Properties EXTREMELY FLAMMABLE

Explosive Properties No data available

Oxidizing Properties No data available

Other information

VOC Content (%) 8703A Dk Blue/Steel Blue: 95.59%

8704A Red/Steel Red: 93.89%

VOC (g/l) 8703A Dk Blue/Steel Blue: 808 g/L

8704A Red/Steel Red: 797 g/L

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Heat, flames and sparks. Incompatible products.

Incompatible materials

Strong oxidizing agents. Strong acids. Strong reducing agents. Strong alkalis.

Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO₂). Soot.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation

Inhalation of vapors in high concentration may cause irritation of respiratory system. May cause drowsiness and dizziness.

Eye Contact

Irritating to eyes. Causes serious eye damage.

Skin Contact

May cause irritation.

Ingestion

May be harmful if swallowed. Ingestion may cause nausea and vomiting.

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethanol	= 7060 mg/kg (Rat)	-	= 124.7 mg/L (Rat) 4 h
n-Butyl acetate	= 10768 mg/kg (Rat)	> 17600 mg/kg (Rabbit)	= 391 ppm (Rat) 4 h
Butane	-	-	658 mg/L (Rat) 4 h
Propane	-	-	= 658 mg/L (Rat) 4 h
n-Butyl alcohol	= 790 mg/kg (Rat)	= 3400 mg/kg (Rabbit)	= 8000 ppm (Rat) 4 h
Diacetone alcohol	= 4 g/kg (Rat)	= 13500 mg/kg (Rabbit)	-
Isopropyl alcohol	= 4396 mg/kg (Rat)	12800 mg/kg (Rat) 12870 mg/kg (Rabbit)	72.6 mg/L (Rat) 4 h
n-Propyl acetate	= 9370 mg/kg (Rat)	> 17760 mg/kg (Rabbit)	-
Basic green 4	= 380 mg/kg (Rat)	-	-

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Delayed and immediate effects and also chronic effects from short and long term exposure

Sensitization No information available.
Mutagenic Effects No information available.
Carcinogenicity Ethanol has been shown to be carcinogenic in long-term studies only when consumed and abused as an alcoholic beverage. The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Ethanol	A3	Group 1	Known	X
Nitrocellulose		Group 2A		X
Isopropyl alcohol		Group 3		

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 3: Not Classifiable as to its Carcinogenicity to Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive Toxicity May damage fertility or the unborn child
STOT - single exposure No information available.
STOT - repeated exposure No information available.
Chronic Toxicity Ethanol has been shown to be a reproductive toxin only when consumed as an alcoholic beverage. Ethanol has been shown to be carcinogenic in long-term studies only when consumed as alcoholic beverage.
Target Organ Effects Respiratory system. Eyes. Skin. Central nervous system (CNS).
Aspiration Hazard No information available.

Numerical measures of toxicity - Product*The following values are calculated based on chapter 3.1 of the GHS document:*

LD50 Oral 5070 mg/kg; Acute toxicity estimate
LD50 Dermal 35146 mg/kg; Acute toxicity estimate
Inhalation
 gas 251736
 dust/mist 63.6 mg/L; Acute toxicity estimate
 Vapor 258.3 mg/L; Acute toxicity estimate

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Ethanol 64-17-5		LC50 96 h: 12.0 - 16.0 mL/L static (Oncorhynchus mykiss) LC50 96 h: > 100 mg/L static (Pimephales promelas) LC50 96 h: 13400 - 15100 mg/L flow-through (Pimephales promelas)	EC50 = 34634 mg/L 30 min EC50 = 35470 mg/L 5 min	LC50 48 h: 9268 - 14221 mg/L (Daphnia magna) EC50 24 h: = 10800 mg/L (Daphnia magna) EC50 48 h: = 2 mg/L Static (Daphnia magna)
n-Butyl acetate 123-86-4	EC50 72 h: = 674.7 mg/L (Desmodesmus subspicatus)	LC50 96 h: 17 - 19 mg/L flow-through (Pimephales promelas) LC50 96 h: = 100 mg/L static (Lepomis macrochirus) LC50 96 h: = 62 mg/L static (Leuciscus idus)	EC50 = 70.0 mg/L 5 min EC50 = 82.2 mg/L 15 min EC50 = 959 mg/L 18 h EC50 = 98.9 mg/L 30 min	EC50 24 h: = 72.8 mg/L (Daphnia magna)
n-Butyl alcohol 71-36-3	EC50 96 h: > 500 mg/L (Desmodesmus subspicatus) EC50 72 h: > 500 mg/L (Desmodesmus subspicatus)	LC50 96 h: 1730 - 1910 mg/L static (Pimephales promelas) LC50 96 h: = 1740 mg/L flow-through (Pimephales promelas) LC50 96 h: 100000 - 500000 µg/L static (Lepomis macrochirus) LC50 96 h: = 1910000 µg/L static (Pimephales promelas)	EC50 = 2041.4 mg/L 5 min EC50 = 2186 mg/L 30 min EC50 = 3980 mg/L 24 h EC50 = 4400 mg/L 17 h	EC50 48 h: = 1983 mg/L (Daphnia magna) EC50 48 h: 1897 - 2072 mg/L Static (Daphnia magna)
Diacetone alcohol 123-42-2		LC50 96 h: = 420 mg/L static (Lepomis macrochirus) LC50 96 h: = 420 mg/L (Lepomis macrochirus)		EC50 24 h: = 8750 mg/L (Daphnia magna)
Isopropyl alcohol 67-63-0	EC50 96 h: > 1000 mg/L (Desmodesmus subspicatus) EC50 72 h: > 1000 mg/L (Desmodesmus subspicatus)	LC50 96 h: = 11130 mg/L static (Pimephales promelas) LC50 96 h: = 9640 mg/L flow-through (Pimephales promelas) LC50 96 h: > 1400000 µg/L (Lepomis macrochirus)		EC50 48 h: = 13299 mg/L (Daphnia magna)
n-Propyl acetate 109-60-4		LC50 96 h: 56-64 mg/L flow-through (Pimephales promelas) LC50 96 h: 56-64 mg/L static (Pimephales promelas)		EC50 24 h: = 318 mg/L (Daphnia magna)

Persistence and Degradability No information available.**Bioaccumulation**

Chemical Name	Log Pow
Ethanol	-0.32
n-Butyl acetate	1.81
Butane	2.89
n-Butyl alcohol	0.785
Diacetone alcohol	1.03
Isopropyl alcohol	0.05

Other Adverse Effects

No information available.

13. DISPOSAL CONSIDERATIONS**Waste Disposal Methods** Dispose of in accordance with local regulations.**Contaminated Packaging** Do not re-use empty containers.

US EPA Waste Number U031

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
n-Butyl alcohol - 71-36-3		Included in waste stream: F039		U031

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Ethanol	Toxic Ignitable
n-Butyl acetate	Toxic
n-Butyl alcohol	Toxic
Nitrocellulose	Ignitable Reactive
Isopropyl alcohol	Toxic Ignitable
n-Propyl acetate	Toxic Ignitable
Xanthylum,9-(2-carboxyphenyl)-3,6-bis(diethyl amino)-, hydrogenbis[3-[(4,5-dihydro-3-methyl-5...	Toxic Corrosive Ignitable

14. TRANSPORT INFORMATION

DOT

UN-Number UN1950
 Proper shipping name Aerosols
 Hazard Class 2.1
 Description UN1950, Aerosols, 2.1
 Emergency Response Guide Number 126

TDG

UN-Number UN1950
 Proper Shipping Name Aerosols
 Hazard Class 2.1
 Description UN1950, Aerosols, 2.1

MEX

UN-Number UN1950
 Proper Shipping Name Aerosols
 Hazard Class 2.1
 Description UN1950, Aerosols, 2.1

ICAO

UN-Number UN1950
 Proper shipping name Aerosols
 Hazard Class 2.1
 Description UN1950, Aerosols, 2.1

IATA

UN-Number UN1950
 Proper Shipping Name Aerosols, flammable
 Hazard Class 2.1
 ERG Code 10L
 Description UN1950, Aerosols, flammable, 2.1

IMDG/IMO

UN-Number UN1950
 Proper Shipping Name Aerosols
 Hazard Class 2

Subsidiary Class	See SP63
EmS No.	F-D, S-U
Description	UN1950, Aerosols, 2.1 (See SP63), (11.667°C c.c.)

RID

UN-Number	UN1950
Proper Shipping Name	Aerosols
Hazard Class	2
Classification Code	5F
Description	UN1950, Aerosols, 2.1

ADR

UN-Number	UN1950
Proper Shipping Name	Aerosols
Hazard Class	2
Classification Code	5F
Tunnel Restriction Code	(D)
Description	UN1950, Aerosols, 2.1, (D)

ADN

Proper Shipping Name	Aerosols
Hazard Class	2
Classification Code	5F
Special Provisions	190, 327, 344, 625
Description	UN1950, Aerosols, 2.1
Limited Quantity	1 L
Ventilation	VE01, VE04

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
-------------	----------

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
n-Butyl alcohol	71-36-3	8.23	1.0
Isopropyl alcohol	67-63-0	2.6575	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	Yes
Reactive Hazard	No

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
n-Butyl acetate	5000 lb			X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
n-Butyl acetate	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
n-Butyl alcohol	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

U.S. State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals: Ethyl alcohol is only considered a Proposition 65 developmental hazard when it is ingested as an alcoholic beverage.

Chemical Name	CAS-No	California Prop. 65
Ethanol	64-17-5	Developmental
Michler's ketone	90-94-8	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Ethanol	X	X	X		
n-Butyl acetate	X	X	X		X
Butane	X	X	X		X
Propane	X	X	X		X
n-Butyl alcohol	X	X	X		X
Diacetone alcohol	X	X	X		X
Nitrocellulose	X	X	X		X
Isopropyl alcohol	X	X	X		X
n-Propyl acetate	X	X	X		X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION

<u>NFPA</u>	Health Hazard 2	Flammability 4	Instability 0	Physical and Chemical Hazards -
<u>HMIS</u>	Health Hazard 2*	Flammability 4	Physical Hazard 0	Personal Protection X

*Indicates a chronic health hazard.

Prepared By

Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Issuing Date

09-Apr-2014

Revision Date

19-Feb-2015

Revision Note

(M)SDS sections updated: 2, 15, 16.

General Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet