

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 10/18/2013 Revision date: 10/13/2017 Supersedes: 02/22/2016

### **SECTION 1: Identification**

Identification

Product form : Substance

Substance name Chromium Trioxide, ACS

CAS-No. 1333-82-0 Product code : LC13090 Formula : CrO3

Synonyms chromia / chromium (VI) oxide / chromic anhydride / chromic trioxide / chromic acid / chromium

anhydride / chromium oxide,red / monochromium oxide / red oxide of chromium

Version: 1.4

Recommended use and restrictions on use

Oxidant Use of the substance/mixture

Reagent

Not for food, drug or household use Restrictions on use

1.3. Supplier

LabChem Inc

Jackson's Pointe Commerce Park Building 1000, 1010 Jackson's Pointe Court

Zelienople, PA 16063 - USA T 412-826-5230 - F 724-473-0647 info@labchem.com - www.labchem.com

**Emergency telephone number** 

Emergency number : CHEMTREC: 1-800-424-9300 or 011-703-527-3887

### SECTION 2: Hazard(s) identification

### Classification of the substance or mixture

### **GHS-US** classification

Oxidizing solids Category 1 H271 May cause fire or explosion; strong oxidizer

Acute toxicity (oral) H301 Toxic if swallowed

Category 3 Acute toxicity (dermal) H311 Toxic in contact with skin

Category 3

Acute toxicity H330 Fatal if inhaled

(inhalation:dust,mist) Category 2

Skin corrosion/irritation H314

Causes severe skin burns and eye damage Category 1A

Respiratory sensitization, May cause allergy or asthma symptoms or breathing difficulties if inhaled H334

Category 1

Skin sensitization, Category H317 May cause an allergic skin reaction

Germ cell mutagenicity H340 May cause genetic defects

Category 1B

Carcinogenicity Category H350 May cause cancer (Inhalation)

Reproductive toxicity Suspected of damaging fertility or the unborn child H361

Category 2

Specific target organ H372 Causes damage to organs (kidneys, liver, respiratory system, Skin, eyes) through prolonged

toxicity (repeated exposure) or repeated exposure Category 1

Hazardous to the aquatic H400 Very toxic to aquatic life

environment - Acute Hazard Category 1

Hazardous to the aquatic H410 Very toxic to aquatic life with long lasting effects environment - Chronic

Hazard Category 1

Full text of H statements: see section 16

11/15/2017 EN (English US) Page 1

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### GHS Label elements, including precautionary statements

#### **GHS-US** labeling

Hazard pictograms (GHS-US)



GHS03









Signal word (GHS-US)

Hazard statements (GHS-US)

: Danger

: H271 - May cause fire or explosion; strong oxidizer H301+H311 - Toxic if swallowed or in contact with skin H314 - Causes severe skin burns and eye damage

H317 - May cause an allergic skin reaction

H330 - Fatal if inhaled

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled

H340 - May cause genetic defects H350 - May cause cancer (Inhalation)

H361 - Suspected of damaging fertility or the unborn child

H372 - Causes damage to organs (kidneys, liver, respiratory system, Skin, eyes) through

prolonged or repeated exposure

H410 - Very toxic to aquatic life with long lasting effects

Precautionary statements (GHS-US)

P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood

P210 - Keep away from heat, sparks, open flames. - No smoking P220 - Keep/Store away from clothing, combustible materials P221 - Take any precaution to avoid mixing with combustibles

P260 - Do not breathe dust

P264 - Wash exposed skin thoroughly after handling P270 - Do not eat, drink or smoke when using this product P271 - Use only outdoors or in a well-ventilated area

P272 - Contaminated work clothing should not be allowed out of the workplace

P273 - Avoid release to the environment

P280 - Wear protective gloves, protective clothing, eye protection, face protection

P283 - Wear fire/flame resistant/retardant clothing

P284 - Wear respiratory protection

P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting

P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated

clothing. Rinse skin with water/shower

P304+P341 - If inhaled: If breathing is difficult, remove person to fresh air and keep

comfortable for breathing

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P306+P360 - If on clothing: Rinse immediately contaminated clothing and skin with plenty of

water before removing clothes

P308+P313 - IF exposed or concerned: Get medical advice/attention

P310 - Immediately call a poison center or doctor/physician

P342+P311 - If experiencing respiratory symptoms: Call a POISON CENTER or

doctor/physician

P361+P364 - Take off immediately all contaminated clothing and wash it before reuse

P363 - Wash contaminated clothing before reuse

P370+P378 - In case of fire: Use carbon dioxide (CO2), powder, alcohol-resistant foam to

P371+P380+P375 - In case of major fire and large quantities: Evacuate area. Fight fire

remotely due to the risk of explosion

P391 - Collect spillage

P403+P233 - Store in a well-ventilated place. Keep container tightly closed

P405 - Store locked up

P501 - Dispose of contents/container to comply with local, state and federal regulations

### Other hazards which do not result in classification

Other hazards not contributing to the classification

: None.

### **Unknown acute toxicity (GHS US)**

Not applicable

11/15/2017 EN (English US) 2/11

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### **SECTION 3: Composition/Information on ingredients**

### 3.1. Substances

Substance type : Mono-constituent

Name	Product identifier	%	GHS-US classification
Chromium Trioxide, ACS (Main constituent)	(CAS-No.) 1333-82-0	100	Ox. Sol. 1, H271 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 2 (Inhalation), H330 Acute Tox. 2 (Inhalation:dust,mist), H330 Skin Corr. 1A, H314 Resp. Sens. 1, H3317 Muta. 1B, H340 Carc. 1A, H350 Repr. 2, H361 STOT RE 1, H372 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of hazard classes and H-statements : see section 16

#### 3.2. Mixtures

Not applicable

### **SECTION 4: First-aid measures**

#### 4.1. Description of first aid measures

First-aid measures general	
----------------------------	--

: Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with labored breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital.

First-aid measures after inhalation

Remove the victim into fresh air. Immediately consult a doctor/medical service.

First-aid measures after skin contact

: Wash immediately with lots of water (15 minutes)/shower. Do not apply (chemical) neutralizing agents. Remove clothing while washing. Do not remove clothing if it sticks to the skin. Cover wounds with sterile bandage. Consult a doctor/medical service. If burned surface > 10%: take victim to hospital.

First-aid measures after eye contact

Rinse immediately with plenty of water for 15 minutes. Do not apply neutralizing agents. Take victim to an ophthalmologist.

First-aid measures after ingestion

Rinse mouth with water. Immediately after ingestion: give lots of water to drink. Do not induce vomiting. Immediately consult a doctor/medical service. Call Poison Information Centre (www.big.be/antigif.htm). Take the container/vomit to the doctor/hospital. Ingestion of large quantities: immediately to hospital. Do not give chemical antidote.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation

: Dry/sore throat. Coughing. Corrosion of the upper respiratory tract. Runny nose. Respiratory difficulties. FOLLOWING SYMPTOMS MAY APPEAR LATER: Possible laryngeal spasm/oedema. Risk of lung edema.

Symptoms/effects after skin contact

: Caustic burns/corrosion of the skin.

Symptoms/effects after eye contact

: Corrosion of the eye tissue. Inflammation/damage of the eye tissue.

Symptoms/effects after ingestion

: Nausea. Burns to the gastric/intestinal mucosa. Abdominal pain. Blood in vomit. Blood in stool. Shock. Disturbances of consciousness. FOLLOWING SYMPTOMS MAY APPEAR LATER: Change in urine output. Renal disease. Enlargement/disease of the liver. Change in the blood composition.

Chronic symptoms

: ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Skin rash/inflammation. Affection of the nasal septum. Nosebleeding. Respiratory difficulties. Possible inflammation of the respiratory tract. Risk of pneumonia. Lung tissue affection/degeneration. Inflammation/damage of the eye tissue. Enlargement/affection of the liver.

### 4.3. Immediate medical attention and special treatment, if necessary

No additional information available

### **SECTION 5: Fire-fighting measures**

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Adapt extinguishing media to the environment.

Unsuitable extinguishing media : No unsuitable extinguishing media known.

11/15/2017 EN (English US) 3/11

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 5.2. Specific hazards arising from the chemical

Fire hazard

: DIRECT FIRE HAZARD. Non combustible. INDIRECT FIRE HAZARD. Promotes combustion. Reactions involving a fire hazard: see "Reactivity Hazard".

Explosion hazard

: INDIRECT EXPLOSION HAZARD. Reactions with explosion hazards: see "Reactivity Hazard".

Reactivity

: Reacts on exposure to water (moisture) with (some) metals. Reacts violently on exposure to water (moisture) with (some) bases. When decomposing on exposure to temperature rise: oxidation which increases fire hazard. Risk of explosion with combustible materials. Reacts with organic material: risk of spontaneous ignition. Reacts violently with many compounds e.g.: with (strong) reducers, with (some) acids and with oils/fats: (increased) risk of fire/explosion.

### 5.3. Special protective equipment and precautions for fire-fighters

Precautionary measures fire

: Exposure to fire/heat: keep upwind. Exposure to fire/heat: consider evacuation. Exposure to fire/heat: have neighbourhood close doors and windows.

Firefighting instructions

: Cool tanks/drums with water spray/remove them into safety. Do not move the load if exposed to heat. Take account of toxic fire-fighting water. Use water moderately and if possible collect or contain it.

Protection during firefighting

: Heat/fire exposure: compressed air/oxygen apparatus.

### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

### 6.1.1. For non-emergency personnel

Protective equipment

: Gloves. Face-shield. Corrosion-proof suit. Dust cloud production: compressed air/oxygen apparatus. Dust cloud production: dust-tight suit. See "Material-Handling" to select protective clothing.

**Emergency procedures** 

Mark the danger area. Prevent dust cloud formation, e.g. by wetting. No naked flames. Corrosion-proof appliances. Keep containers closed. Wash contaminated clothes. In case of reactivity hazard: consider evacuation.

Measures in case of dust release

: In case of dust production: keep upwind. In case of dust production: consider evacuation. Dust production: have neighbourhood close doors and windows.

### 6.1.2. For emergency responders

Protective equipment

: Do not breathe dust. Equip cleanup crew with proper protection.

Emergency procedures

: If a major spill occurs, all personnel should be immediately evacuated and the area ventilated. Stop leak if safe to do so. Ventilate area.

### 6.2. Environmental precautions

Prevent soil and water pollution. Prevent spreading in sewers.

### 6.3. Methods and material for containment and cleaning up

For containment

: Contain released substance, pump into suitable containers. Consult "Material-handling" to select material of containers. Plug the leak, cut off the supply. Dam up the solid spill. Knock down/dilute dust cloud with water spray. Take account of toxic/corrosive precipitation water.

Methods for cleaning up

: Spill must not return in its original container. Prevent dispersion by covering with dry sand/earth. Do not take up in combustible material such as: saw dust. Wetted substance: mix with dry sand or powdered limestone. Scoop solid spill into closing containers. See "Material-handling" for suitable container materials. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

### 6.4. Reference to other sections

No additional information available

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Additional hazards when processed

- : Pulverization rapidly increases toxic concentration.
- Precautions for safe handling

  : Comply with the legal requirements. Remove contaminated clothing immediately. Clean contaminated clothing. Keep the substance free from contamination. Use corrosionproof equipment. Thoroughly clean/dry the installation before use. Do not discharge the waste into the drain. Avoid raising dust. Keep away from naked flames/heat. Observe very strict hygiene avoid contact. Keep container tightly closed. Measure the concentration in the air regularly.

Carry operations in the open/under local exhaust/ventilation or with respiratory protection.

Hygiene measures : Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse.

11/15/2017 EN (English US) 4/11

## Safety Data Sheet

Storage area

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Conditions for safe storage, including any incompatibilities

Incompatible products : aluminum. combustible materials. metals. Strong oxidizers. Strong reducing agents.

Incompatible materials

Heat-ignition : KEEP SUBSTANCE AWAY FROM: heat sources.

Prohibitions on mixed storage KEEP SUBSTANCE AWAY FROM: combustible materials. reducing agents. (strong) bases.

oils-fats. metals. halogens. organic materials. alcohols. strong acids.

Store in a dry area. Store in a dark area. Keep container in a well-ventilated place. Fireproof storeroom. Keep locked up. Unauthorized persons are not admitted. Detached building. Keep

only in the original container. Meet the legal requirements.

SPECIAL REQUIREMENTS: hermetical. watertight. corrosion-proof. dry. clean. shock-Special rules on packaging

absorbing, correctly labelled, meet the legal requirements. Secure fragile packagings in solid

containers.

Packaging materials : MATERIAL TO AVOID: paper. wood. steel. aluminium. iron. copper. nickel. bronze. plastics.

### **SECTION 8: Exposure controls/personal protection**

#### Control parameters

Chromium Trioxide, ACS (1333-82-0)		
ACGIH	ACGIH TWA (mg/m³)	0.05 mg/m³ (Chromium, water-soluble inorgan. Cr VI compounds; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
OSHA	OSHA PEL (TWA) (mg/m³)	0.005 mg/m³
IDLH	US IDLH (mg/m³)	15 mg/m³
NIOSH	NIOSH REL (TWA) (mg/m³)	0.001 mg/m³

### Appropriate engineering controls

Appropriate engineering controls

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Provide adequate general and local exhaust ventilation.

### Individual protection measures/Personal protective equipment

### Personal protective equipment:

Safety glasses. Gloves. Protective clothing. High dust production: self-contained breathing apparatus. Combined gas/dust mask with filter type











### Materials for protective clothing:

GIVE GOOD RESISTANCE: butyl rubber. PVC

Hand protection:

Gloves

#### Eye protection:

Face shield. In case of dust production: protective goggles

## Skin and body protection:

Corrosion-proof clothing. In case of dust production: head/neck protection

### Respiratory protection:

Dust production: dust mask with filter type P3. High dust production: self-contained breathing

apparatus

11/15/2017 EN (English US) 5/11

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state : Solid

Appearance : Crystalline solid. Crystalline powder. Needles. Flakes.

Color : Dark red to red-violet

Odor : Odorless

Odor threshold : No data available pH : No data available

Melting point : 196 °C

Freezing point : No data available
Boiling point : Not applicable
Flash point : Not applicable
Relative evaporation rate (butyl acetate=1) : No data available
Flammability (solid, gas) : No data available
Vapor pressure : < 0.1 hPa (20 °C)
Relative vapor density at 20 °C : No data available

Relative density : 2.7
Specific gravity / density : 2700 kg/m³

Molecular mass : 99.99 g/mol

Solubility : Exothermically soluble in water. Soluble in ethanol. Soluble in ether. Soluble in acids. Soluble in

nitric acid. Soluble in sulfuric acid.

Water: 62 g/100ml

Log Pow : No data available
Auto-ignition temperature : Not applicable
Decomposition temperature : > 196 °C
Viscosity, kinematic : No data available

Viscosity, dynamic : No data available Explosion limits : No data available

Explosive properties : May cause fire or explosion; strong oxidiser.

Oxidizing properties : May cause fire or explosion; strong oxidiser.

### 9.2. Other information

SADT : Not applicable

VOC content : 0 %

Other properties : Hygroscopic. Substance has acid reaction.

### **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

Reacts on exposure to water (moisture) with (some) metals. Reacts violently on exposure to water (moisture) with (some) bases. When decomposing on exposure to temperature rise: oxidation which increases fire hazard. Risk of explosion with combustible materials. Reacts with organic material: risk of spontaneous ignition. Reacts violently with many compounds e.g.: with (strong) reducers, with (some) acids and with oils/fats: (increased) risk of fire/explosion.

### 10.2. Chemical stability

Unstable on exposure to moisture.

### 10.3. Possibility of hazardous reactions

May react violently with reducing agents.

### 10.4. Conditions to avoid

Avoid dust formation. Finely divided metals. Incompatible materials. Moisture.

### 10.5. Incompatible materials

alcohols. Aldehydes. aluminum. combustible materials. metals. Strong reducing agents. Strong bases.

## 10.6. Hazardous decomposition products

No additional information available

11/15/2017 EN (English US) 6/11

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

Likely routes of exposure : Inhalation; Skin and eye contact

Acute toxicity : Oral: Toxic if swallowed. Dermal: Toxic in contact with skin. Inhalation: Fatal if inhaled.

Inhalation:dust,mist: Fatal if inhaled.

Chromium Trioxide, ACS (1333-82-0)	
LD50 oral rat	50 mg/kg (Rat)
LD50 dermal rat	55 mg/kg (Rat)
LD50 dermal rabbit	57 mg/kg (Rabbit)
LC50 inhalation rat (mg/l)	0.217 mg/l/4h (Rat)
ATE US (oral)	50 mg/kg body weight
ATE US (dermal)	55 mg/kg body weight
ATE US (gases)	100 ppmV/4h
ATE US (vapors)	0.217 mg/l/4h
ATE US (dust, mist)	0.217 mg/l/4h
Additional information	An oral toxicity study of chromium trioxide conducted on rats in 1989 found the average LD50 to be 51.9 mg/kg.

Skin corrosion/irritation : Causes severe skin burns and eye damage.

Serious eye damage/irritation : Not classified

Respiratory or skin sensitization : May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an

allergic skin reaction.

Germ cell mutagenicity : May cause genetic defects.

Carcinogenicity : May cause cancer (Inhalation).

Chromium Trioxide, ACS (1333-82-0)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.

Specific target organ toxicity – single exposure : Not classified

Specific target organ toxicity – repeated

exposure

: Causes damage to organs (kidneys, liver, respiratory system, Skin, eyes) through prolonged or repeated exposure.

Aspiration hazard : Not classified

Symptoms/effects after inhalation : Dry/sore throat. Coughing. Corrosion of the upper respiratory tract. Runny nose. Respiratory

difficulties. FOLLOWING SYMPTOMS MAY APPEAR LATER: Possible laryngeal

spasm/oedema. Risk of lung edema.

Symptoms/effects after skin contact : Caustic burns/corrosion of the skin.

Symptoms/effects after eye contact : Corrosion of the eye tissue. Inflammation/damage of the eye tissue.

Symptoms/effects after ingestion : Nausea. Burns to the gastric/intestinal mucosa. Abdominal pain. Blood in vomit. Blood in stool. Shock. Disturbances of consciousness. FOLLOWING SYMPTOMS MAY APPEAR LATER:

Shock. Disturbances of consciousness. FOLLOWING SYMPTOMS MAY APPEAR LATER: Change in urine output. Renal disease. Enlargement/disease of the liver. Change in the blood

composition.

Chronic symptoms : ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Skin rash/inflammation. Affection of

the nasal septum. Nosebleeding. Respiratory difficulties. Possible inflammation of the respiratory tract. Risk of pneumonia. Lung tissue affection/degeneration. Inflammation/damage

of the eye tissue. Enlargement/affection of the liver.

### **SECTION 12: Ecological information**

12.1. Toxicity	
Ecology - general	: Dangerous for the environment.
Ecology - air	: Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009). TA-Luft Klasse 5.2.7.1.1/l.
Ecology - water	: Severe water pollutant (surface water). Maximum concentration in drinking water: 0.050 mg/l (chromium) (Directive 98/83/EC). Highly toxic to aquatic organisms. pH shift.
Chromium Trioxide, ACS (1333-82-0)	
LC50 fish 1	40 mg/l (LC50; 96 h; Colisa fasciatus)
EC50 Daphnia 2	0.01 - 2.5 mg/l (LC50: 96 h)

11/15/2017 EN (English US) 7/11

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 12.2. Persistence and degradability

Chromium Trioxide, ACS (1333-82-0)	
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable

### 12.3. Bioaccumulative potential

Chromium Trioxide, ACS (1333-82-0)	
BCF fish 1	4.6 - 72 (BCF)
BCF fish 2	16 (BCF)
BCF other aquatic organisms 1	192 (BCF)
BCF other aquatic organisms 2	125 (BCF)
Bioaccumulative potential	Not bioaccumulative.

#### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

No additional information available

## **SECTION 13: Disposal considerations**

#### 13.1. Disposal methods

Waste disposal recommendations

- : Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Recycle/reuse. Remove for physico-chemical/biological treatment. Remove to an authorized dump (Class I). Treat using the best available techniques before discharge into drains or the aquatic environment.
- Additional information : LWCA (the Netherlands): KGA category 06. Hazardous waste according to Directive 2008/98/EC.

## **SECTION 14: Transport information**

### **Department of Transportation (DOT)**

In accordance with DOT

Transport document description : UN1463 Chromium trioxide, anhydrous, 5.1, II

UN-No.(DOT) : UN1463

Proper Shipping Name (DOT) : Chromium trioxide, anhydrous

Packing group (DOT) : II - Medium Danger

Hazard labels (DOT) : 5.1 - Oxidizer

6.1 - Poison inhalation hazard

8 - Corrosive



Dangerous for the environment : Yes
Marine pollutant : Yes



DOT Packaging Non Bulk (49 CFR 173.xxx) : 212

11/15/2017 EN (English US) 8/11

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Packaging Bulk (49 CFR 173.xxx)

: 242

DOT Special Provisions (49 CFR 172.102)

: IB8 - Authorized IBCs: Metal (11A, 11B, 11N, 21A, 21B, 21N, 31A, 31B and 31N); Rigid plastics (11H1, 11H2, 21H1, 21H2, 31H1 and 31H2); Composite (11HZ1, 11HZ2, 21HZ1, 21HZ2, 31HZ1 and 31HZ2); Fiberboard (11G); Wooden (11C, 11D and 11F); Flexible (13H1,

13H2, 13H3, 13H4, 13H5, 13L1, 13L2, 13L3, 13L4, 13M1 or 13M2).

IP2 - When IBCs other than metal or rigid plastics IBCs are used, they must be offered for transportation in a closed freight container or a closed transport vehicle.

IP4 - Flexible, fiberboard or wooden IBCs must be sift-proof and water-resistant or be fitted with a sift-proof and water-resistant liner.

T3 - 2.65 178.274(d)(2) Normal..... 178.275(d)(2)

TP33 - The portable tank instruction assigned for this substance applies for granular and powdered solids and for solids which are filled and discharged at temperatures above their melting point which are cooled and transported as a solid mass. Solid substances transported or offered for transport above their melting point are authorized for transportation in portable tanks conforming to the provisions of portable tank instruction T4 for solid substances of packing group III or T7 for solid substances of packing group II, unless a tank with more stringent requirements for minimum shell thickness, maximum allowable working pressure. pressure-relief devices or bottom outlets are assigned in which case the more stringent tank instruction and special provisions shall apply. Filling limits must be in accordance with portable tank special provision TP3. Solids meeting the definition of an elevated temperature material must be transported in accordance with the applicable requirements of this subchapter.

DOT Packaging Exceptions (49 CFR 173.xxx) DOT Quantity Limitations Passenger aircraft/rail : 5 kg

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 25 kg

CFR 175.75)

**DOT Vessel Stowage Location** : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

**DOT Vessel Stowage Other** : 66 - Stow "separated from" flammable solids,90 - Stow "separated from" radioactive materials

Other information : No supplementary information available.

### **SECTION 15: Regulatory information**

### 15.1. US Federal regulations

Chromium Trioxide, ACS (1333-82-0)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313		
EPA TSCA Regulatory Flag	R - R - indicates a substance that is the subject of a Section 6 risk management rule under TSCA.	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	10 lb	
SARA Section 311/312 Hazard Classes	Physical hazard - Oxidizer (liquid, solid or gas) Health hazard - Acute toxicity (any route of exposure) Health hazard - Carcinogenicity Health hazard - Respiratory or skin sensitization Health hazard - Germ cell mutagenicity Health hazard - Reproductive toxicity Health hazard - Serious eye damage or eye irritation Health hazard - Skin corrosion or Irritation Health hazard - Specific target organ toxicity (single or repeated exposure)	

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Chromium Trioxide, ACS	CAS-No. 1333-82-0	100%
------------------------	-------------------	------

#### 15.2. International regulations

#### **CANADA**

No additional information available

### **EU-Regulations**

No additional information available

11/15/2017 EN (English US) 9/11

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### **National regulations**

No additional information available

15.3. US State regulations

Chromium Trioxide, ACS (1333-82-0)	
U.S California - Proposition 65 - Carcinogens List	Yes
U.S California - Proposition 65 - Developmental Toxicity	Yes
U.S California - Proposition 65 - Reproductive Toxicity - Female	Yes
U.S California - Proposition 65 - Reproductive Toxicity - Male	Yes
No significant risk level (NSRL)	0.001 μg/day

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer, developmental and/or reproductive harm

### SECTION 16: Other information

Revision date : 10/13/2017

Full text of H-phrases: see section 16:

NFPA reactivity


H271	May cause fire or explosion; strong oxidizer
H301	Toxic if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H330	Fatal if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H340	May cause genetic defects
H350	May cause cancer
H361	Suspected of damaging fertility or the unborn child
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

NFPA health hazard	: 3 - Materials that, under emergency conditions, can cause serious or permanent injury.
NFPA fire hazard	: 0 - Materials that will not burn under typical dire conditions, including intrinsically noncombustible materials such as

concrete, stone, and sand.

: 1 - Materials that in themselves are normally stable but can become unstable at elevated temperatures and pressures.

NFPA specific hazard : OX - Materials that posses oxidizing properties.



11/15/2017 EN (English US) 10/11

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is

given

Flammability : 0 Minimal Hazard - Materials that will not burn

Physical : 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high

temperatures and pressures. Materials may react non-violently with water or undergo

hazardous polymerization in the absence of inhibitors.

Personal protection :

J - Splash goggles, Gloves, Synthetic apron, Dust & vapor respirator

SDS US LabChem

Information in this SDS is from available published sources and is believed to be accurate. No warranty, express or implied, is made and LabChem Inc assumes no liability resulting from the use of this SDS. The user must determine suitability of this information for his application.

11/15/2017 EN (English US) 11/11