




SAFETY DATA SHEET

1. Identification

Product identifier	Liquid Wrench Hydraulic Jack Oil		
Other means of identification			
SDS number	M3312		
Part No.	M3332, M3312		
Tariff code	2710.19.3040		
Recommended use	Hydraulic Fluid		
Recommended restrictions	None known.		
Manufacturer/Importer/Supplier/Distributor information			
Manufacturer			
Company name	Blumenthal Brands Integrated, LLC		
Address	600 Radiator Road Indian Trail, NC 28079		
Telephone	Customer Service	(704) 821-7643	
	Technical	(704) 821-7643	
Website	www.solvewithB.com		
E-mail	sds@solvewithB.com		
Emergency phone number	Poison Control (RMPDC)	(303) 623-5716	
	Poison Control (RMPDC)	(877) 740-5015	

2. Hazard(s) identification

Physical hazards	Not classified.		
Health hazards	Reproductive toxicity (fertility, the unborn child)	Category 1A	
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 1	
	Hazardous to the aquatic environment, long-term hazard	Category 1	
OSHA defined hazards	Not classified.		
Label elements			
Signal word	Danger		
Hazard statement	May be harmful if swallowed and enters airways. May damage fertility. May damage the unborn child. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.		
Precautionary statement			
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.		
Response	If exposed or concerned: Get medical advice/attention. Collect spillage.		
Storage	Store locked up.		
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.		
Hazard(s) not otherwise classified (HNOC)	None known.		

Supplemental information

NOTE: This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission regulations which take precedence over OSHA Hazard Communication labeling. The container label may not include the OSHA label elements listed in this document. Always carefully review the entire SDS and the product label prior to use in the workplace.

3. Composition/information on ingredients**Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Mineral Oil		Mixture	90 - 100
Calcium Alkaryl Sulfonate		Proprietary	< 0.5
Calcium Long-chain Alkylphenate Sulfide		Proprietary	< 0.5
Long-chain Alkenyl Succinimide		Proprietary	< 0.5
Zinc dialkyldithiophosphate		68649-42-3	< 0.5
Other components below reportable levels			< 1

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Drink 1 or 2 glasses of water. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
--	--

Methods and materials for containment and cleaning up

This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage**Precautions for safe handling**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in tightly closed container. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection**Occupational exposure limits**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Components	Type	Value
CADMIUM (CAS 7440-43-9)	TWA	0.005 mg/m3
ETHYLENE OXIDE (CAS 75-21-8)	STEL	5 ppm
	TWA	1 ppm
LEAD (CAS 7439-92-1)	TWA	0.05 mg/m3

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
1,4-dioxane (CAS 123-91-1)	PEL	360 mg/m3 100 ppm
PROPYLENE OXIDE (CAS 75-56-9)	PEL	240 mg/m3 100 ppm

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value	Form
CADMIUM (CAS 7440-43-9)	Ceiling	0.6 mg/m3	Dust.
		0.3 mg/m3	Fume.
	TWA	0.2 mg/m3	Dust.
		0.1 mg/m3	Fume.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
1,4-dioxane (CAS 123-91-1)	TWA	20 ppm	
CADMIUM (CAS 7440-43-9)	TWA	0.01 mg/m3	
		0.002 mg/m3	Respirable fraction.
ETHYLENE OXIDE (CAS 75-21-8)	TWA	1 ppm	

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
LEAD (CAS 7439-92-1)	TWA	0.05 mg/m3	
PROPYLENE OXIDE (CAS 75-56-9)	TWA	2 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
1,4-dioxane (CAS 123-91-1)	Ceiling	3.6 mg/m3 1 ppm
ETHYLENE OXIDE (CAS 75-21-8)	Ceiling	9 mg/m3 5 ppm
	TWA	0.18 mg/m3 0.1 ppm
LEAD (CAS 7439-92-1)	TWA	0.05 mg/m3

Biological limit values**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
CADMIUM (CAS 7440-43-9)	5 µg/g	Cadmium	Creatinine in urine	*
	5 µg/l	Cadmium	Blood	*
LEAD (CAS 7439-92-1)	200 µg/l	Lead	Blood	*

* - For sampling details, please see the source document.

Exposure guidelines**US - California OELs: Skin designation**

1,4-dioxane (CAS 123-91-1) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

1,4-dioxane (CAS 123-91-1) Skin designation applies.

US - Tennessee OELs: Skin designation

1,4-dioxane (CAS 123-91-1) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

1,4-dioxane (CAS 123-91-1) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

1,4-dioxane (CAS 123-91-1) Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Chemical respirator with organic vapor cartridge and full facepiece. Applicable for industrial settings only.

Skin protection**Hand protection**

Wear appropriate chemical resistant gloves. Applicable for industrial settings only.

Other

Use of an impervious apron is recommended. Applicable for industrial settings only.

Respiratory protection

Chemical respirator with organic vapor cartridge and full facepiece. Chemical respirator with organic vapor cartridge and full facepiece if threshold limits are exceeded. Applicable for industrial settings only.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance Liquid Clear.

Physical state	Liquid.
Form	Liquid.
Color	Colorless.
Odor	Mild Petroleum
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	> 410.0 °F (> 210.0 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	0.013 torr @ 25C
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	6.9 cSt
Viscosity temperature	212 °F (100 °C)
Other information	
Density	0.9 g/ml @ 15.6 C
Explosive properties	Not explosive.
Flammability class	Combustible IIIB estimated
Kinematic viscosity	31.7 mm²/s
Kinematic viscosity temperature	104 °F (40 °C)
Oxidizing properties	Not oxidizing.
Percent volatile	0.3 % estimated
Pour point	-40 °F (-40 °C)
Specific gravity	0.9
VOC	0.35 % estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.

Hazardous decomposition products

No hazardous decomposition products are known.

11. Toxicological information**Information on likely routes of exposure**

Inhalation	Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Information on toxicological effects**Acute toxicity**

Components	Species	Test Results
1,4-dioxane (CAS 123-91-1)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	7600 mg/kg
Inhalation		
LC50	Rat	46 mg/l, 2 Hours
Oral		
LD50	Rat	5150 mg/kg
CADMIUM (CAS 7440-43-9)		
<u>Acute</u>		
Oral		
LD50	Rat	63 - 259 mg/kg
ETHYLENE OXIDE (CAS 75-21-8)		
<u>Acute</u>		
Inhalation		
LC50	Rat	1450 ppm, 4 Hours
Oral		
LD50	Rat	72 mg/kg
LEAD (CAS 7439-92-1)		
<u>Acute</u>		
Dermal		
LD50	Rat	> 2000 mg/kg, 24 Hours
Inhalation		
LC50	Rat	> 5.05 mg/l, 4 Hours
Oral		
LD50	Rat	> 2000 mg/kg
PROPYLENE OXIDE (CAS 75-56-9)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	950 - 1250 mg/kg, 4 Hours
Inhalation		
LC50	Mouse	1740 ppm, 4 Hours
Oral		
LD50	Rat	380 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.**Serious eye damage/eye irritation** Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization**ACGIH sensitization**

PROPYLENE OXIDE (CAS 75-56-9)

Dermal sensitization

Respiratory sensitization Not a respiratory sensitizer.**Skin sensitization** This product is not expected to cause skin sensitization.**Germ cell mutagenicity** No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.**Carcinogenicity** Not classifiable as to carcinogenicity to humans.**IARC Monographs. Overall Evaluation of Carcinogenicity**

1,4-dioxane (CAS 123-91-1)

2B Possibly carcinogenic to humans.

CADMIUM (CAS 7440-43-9)

1 Carcinogenic to humans.

ETHYLENE OXIDE (CAS 75-21-8)

1 Carcinogenic to humans.

LEAD (CAS 7439-92-1)

2B Possibly carcinogenic to humans.

PROPYLENE OXIDE (CAS 75-56-9)

2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

CADMIUM (CAS 7440-43-9)

Cancer

ETHYLENE OXIDE (CAS 75-21-8)

Cancer

US. National Toxicology Program (NTP) Report on Carcinogens

1,4-dioxane (CAS 123-91-1)

Reasonably Anticipated to be a Human Carcinogen.

CADMIUM (CAS 7440-43-9)

Known To Be Human Carcinogen.

ETHYLENE OXIDE (CAS 75-21-8)

Known To Be Human Carcinogen.

LEAD (CAS 7439-92-1)

Reasonably Anticipated to be a Human Carcinogen.

PROPYLENE OXIDE (CAS 75-56-9)

Reasonably Anticipated to be a Human Carcinogen.

Reproductive toxicity May damage fertility. May damage the unborn child.**Specific target organ toxicity - single exposure** Not classified.**Specific target organ toxicity - repeated exposure** Not classified.**Aspiration hazard** Not an aspiration hazard.**Chronic effects** Prolonged inhalation may be harmful.**12. Ecological information****Ecotoxicity** Very toxic to aquatic life with long lasting effects.

Components			Species	Test Results
1,4-dioxane (CAS 123-91-1)				
Aquatic				
Fish	LC50		Inland silverside (Menidia beryllina)	6700 mg/l, 96 hours
CADMIUM (CAS 7440-43-9)				
Aquatic				
Crustacea	EC50		Water flea (Daphnia magna)	0.0491 mg/l, 48 hours
Fish	LC50		Rainbow trout,donaldson trout (Oncorhynchus mykiss)	0.0024 - 0.0029 mg/l, 96 hours
ETHYLENE OXIDE (CAS 75-21-8)				
Aquatic				
Fish	LC50		Fathead minnow (Pimephales promelas)	73 - 96 mg/l, 96 hours
LEAD (CAS 7439-92-1)				
Aquatic				
Fish	LC50		Rainbow trout,donaldson trout (Oncorhynchus mykiss)	1.17 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.**Bioaccumulative potential****Partition coefficient n-octanol / water (log Kow)**

1,4-dioxane

-0.27

ETHYLENE OXIDE

-0.3

PROPYLENE OXIDE

0.03

Mobility in soil	No data available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	D006: Waste Cadmium D008: Waste Lead The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number	Not available.
UN proper shipping name	Consumer commodity, MARINE POLLUTANT (Petroleum Distillate), Limited Quantity
Transport hazard class(es)	
Class	ORM-D
Subsidiary risk	-
Label(s)	None
Packing group	Not available.
Environmental hazards	
Marine pollutant	Yes
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Packaging exceptions	156, 306
Packaging non bulk	156, 306
Packaging bulk	None

IATA

UN number	UN3082
UN proper shipping name	Environmentally hazardous substance, liquid, n.o.s.
Transport hazard class(es)	
Class	9
Subsidiary risk	-
Packing group	III
Environmental hazards	Yes
ERG Code	9L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.

IMDG

UN number	UN3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., MARINE POLLUTANT (Petroleum Distillate)
Transport hazard class(es)	
Class	9
Subsidiary risk	-
Packing group	III
Environmental hazards	
Marine pollutant	Yes

EmS

F-A, S-F


Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Petroleum Distillate


Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not established.

DOT



IATA; IMDG



Marine pollutant



General information

IMDG Regulated Marine Pollutant. DOT Regulated Marine Pollutant.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

1,4-dioxane (CAS 123-91-1)	Listed.
CADMIUM (CAS 7440-43-9)	Listed.
ETHYLENE OXIDE (CAS 75-21-8)	Listed.
LEAD (CAS 7439-92-1)	Listed.
PROPYLENE OXIDE (CAS 75-56-9)	Listed.
Zinc dialkyldithiophosphate (CAS 68649-42-3)	Listed.

SARA 304 Emergency release notification

ETHYLENE OXIDE (CAS 75-21-8)	10 LBS
PROPYLENE OXIDE (CAS 75-56-9)	100 LBS

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

CADMIUM (CAS 7440-43-9)	Cancer
ETHYLENE OXIDE (CAS 75-21-8)	Cancer
LEAD (CAS 7439-92-1)	Reproductive toxicity

CADMIUM (CAS 7440-43-9)	Lung
ETHYLENE OXIDE (CAS 75-21-8)	Reproductive toxicity
LEAD (CAS 7439-92-1)	Central nervous system
CADMIUM (CAS 7440-43-9)	Kidney
ETHYLENE OXIDE (CAS 75-21-8)	Mutagenicity
LEAD (CAS 7439-92-1)	Kidney
CADMIUM (CAS 7440-43-9)	Acute toxicity
ETHYLENE OXIDE (CAS 75-21-8)	Central nervous system
LEAD (CAS 7439-92-1)	Blood
ETHYLENE OXIDE (CAS 75-21-8)	Skin sensitization
LEAD (CAS 7439-92-1)	Acute toxicity
ETHYLENE OXIDE (CAS 75-21-8)	Skin irritation
	Eye irritation
	respiratory tract irritation
	Acute toxicity
	Flammability

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Chemical name	CAS number	Reportable quantity (pounds)	Threshold planning quantity (pounds)	Threshold planning quantity, lower value (pounds)	Threshold planning quantity, upper value (pounds)
ETHYLENE OXIDE	75-21-8	10	1000		
PROPYLENE OXIDE	75-56-9	100	10000		

SARA 311/312 Hazardous chemical No (Exempt)

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
1,4-dioxane	123-91-1	< 0.2
CADMIUM	7440-43-9	< 0.2
ETHYLENE OXIDE	75-21-8	< 0.2
LEAD	7439-92-1	< 0.2
PROPYLENE OXIDE	75-56-9	< 0.2

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

1,4-dioxane (CAS 123-91-1)
 CADMIUM (CAS 7440-43-9)
 ETHYLENE OXIDE (CAS 75-21-8)
 LEAD (CAS 7439-92-1)
 PROPYLENE OXIDE (CAS 75-56-9)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

ETHYLENE OXIDE (CAS 75-21-8)
 PROPYLENE OXIDE (CAS 75-56-9)

Safe Drinking Water Act (SDWA) Not regulated.

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

ETHYLENE OXIDE (CAS 75-21-8) Other Flavoring Substances with OSHA PEL's

US state regulations

California Proposition 65



WARNING: This product can expose you to chemicals including Ethylene Oxide, which are known to the State of California to cause cancer, and Lead, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

1,4-dioxane (CAS 123-91-1)	Listed: January 1, 1988
CADMIUM (CAS 7440-43-9)	Listed: October 1, 1987
ETHYLENE OXIDE (CAS 75-21-8)	Listed: July 1, 1987
LEAD (CAS 7439-92-1)	Listed: October 1, 1992
PROPYLENE OXIDE (CAS 75-56-9)	Listed: October 1, 1988

California Proposition 65 - CRT: Listed date/Developmental toxin

CADMIUM (CAS 7440-43-9)	Listed: May 1, 1997
-------------------------	---------------------

Ethylene Glycol (CAS 107-21-1)
ETHYLENE OXIDE (CAS 75-21-8)
LEAD (CAS 7439-92-1)

Listed: June 19, 2015
Listed: August 7, 2009
Listed: February 27, 1987

California Proposition 65 - CRT: Listed date/Female reproductive toxin

ETHYLENE OXIDE (CAS 75-21-8)
LEAD (CAS 7439-92-1)

Listed: February 27, 1987
Listed: February 27, 1987

California Proposition 65 - CRT: Listed date/Male reproductive toxin

CADMIUM (CAS 7440-43-9)
ETHYLENE OXIDE (CAS 75-21-8)
LEAD (CAS 7439-92-1)

Listed: May 1, 1997
Listed: August 7, 2009
Listed: February 27, 1987

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

1,4-dioxane (CAS 123-91-1)
CADMIUM (CAS 7440-43-9)
ETHYLENE OXIDE (CAS 75-21-8)
LEAD (CAS 7439-92-1)
PROPYLENE OXIDE (CAS 75-56-9)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 05-01-2015
Revision date 05-29-2019
Version # 02
HMIS® ratings Health: 2
Flammability: 0
Physical hazard: 0

NFPA ratings Health: 2
Flammability: 0
Instability: 0

NFPA ratings



Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision information

This document has undergone significant changes and should be reviewed in its entirety.