

SAFETY DATA SHEET

Creation Date 26-Sep-2009

Revision Date 23-Jan-2018

Revision Number 4

1. Identification

Product Name m-Xylene

Cat No. : AC610470000; AC610471000

CAS-No 108-38-3
Synonyms 1,3-Dimethylbenzene

Recommended Use Laboratory chemicals.
Uses advised against Not for food, drug, pesticide or biocidal product use

Details of the supplier of the safety data sheet**Company**

Fisher Scientific
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410

Emergency Telephone NumberFor information **US** call: 001-800-ACROS-01 / **Europe** call: +32 14 57 52 11Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99**CHEMTREC** Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887**2. Hazard(s) identification****Classification**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

| | |
|------------------------------------|------------|
| Flammable liquids | Category 3 |
| Acute dermal toxicity | Category 4 |
| Acute Inhalation Toxicity - Vapors | Category 4 |
| Skin Corrosion/irritation | Category 2 |
| Serious Eye Damage/Eye Irritation | Category 2 |

Label Elements**Signal Word**

Warning

Hazard Statements

Flammable liquid and vapor
Harmful in contact with skin
Causes skin irritation
Causes serious eye irritation
Harmful if inhaled

**Precautionary Statements****Prevention**

Wear protective gloves/protective clothing/eye protection/face protection

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Wash face, hands and any exposed skin thoroughly after handling

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

Skin

Call a POISON CENTER or doctor/physician if you feel unwell

If skin irritation occurs: Get medical advice/attention

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

Fire

In case of fire: Use CO₂, dry chemical, or foam for extinction

Storage

Store in a well-ventilated place. Keep cool

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

None identified

3. Composition/Information on Ingredients

| Component | CAS-No | Weight % |
|-----------|----------|----------|
| m-Xylene | 108-38-3 | >95 |

4. First-aid measures

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.

Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.

Inhalation

Move to fresh air. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required. If not breathing, give artificial respiration.

| | |
|--|---|
| Ingestion | Do not induce vomiting. Call a physician or Poison Control Center immediately. |
| Most important symptoms and effects | Breathing difficulties. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting |
| Notes to Physician | Treat symptomatically |

5. Fire-fighting measures

| | |
|---|---|
| Suitable Extinguishing Media | Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Cool closed containers exposed to fire with water spray. |
| Unsuitable Extinguishing Media | No information available |
| Flash Point | 25 °C / 77 °F |
| Method - | No information available |
| Autoignition Temperature | 465 °C / 869 °F |
| Explosion Limits | |
| Upper | 7.0% |
| Lower | 1.1% |
| Sensitivity to Mechanical Impact | No information available |
| Sensitivity to Static Discharge | No information available |

Specific Hazards Arising from the Chemical

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO) Carbon dioxide (CO₂)

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

| | | | |
|---------------|---------------------|--------------------|-------------------------|
| Health | Flammability | Instability | Physical hazards |
| 2 | 3 | 0 | N/A |

6. Accidental release measures

| | |
|---|--|
| Personal Precautions | Use personal protective equipment. Remove all sources of ignition. Take precautionary measures against static discharges. |
| Environmental Precautions | Do not flush into surface water or sanitary sewer system. |
| Methods for Containment and Clean Up | Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges. |

7. Handling and storage

| | |
|-----------------|--|
| Handling | Wear personal protective equipment. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Take precautionary measures against static discharges. |
| Storage | Keep containers tightly closed in a dry, cool and well-ventilated place. Flammables area. Keep away from heat and sources of ignition. |

8. Exposure controls / personal protection

Exposure Guidelines

| Component | ACGIH TLV | OSHA PEL | NIOSH IDLH | Mexico OEL (TWA) |
|-----------|-------------------------------|----------|---|--|
| m-Xylene | TWA: 100 ppm STEL: 150 ppm | | IDLH: 900 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 150 ppm STEL: 655 mg/m ³ | TWA: 100 ppm TWA: 435 mg/m ³ STEL: 150 ppm STEL: 655 mg/m ³ |

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location.
Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment.

Personal Protective Equipment**Eye/face Protection**

Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

| | |
|--|---------------------------------|
| Physical State | Liquid |
| Appearance | Colorless |
| Odor | aromatic |
| Odor Threshold | No information available |
| pH | No information available |
| Melting Point/Range | -48 °C / -54.4 °F |
| Boiling Point/Range | 139 - 139 °C / 282.2 - 282.2 °F |
| Flash Point | 25 °C / 77 °F |
| Evaporation Rate | 0.7 |
| Flammability (solid,gas) | Not applicable |
| Flammability or explosive limits | |
| Upper | 7.0% |
| Lower | 1.1% |
| Vapor Pressure | 8 mbar @ 20 °C |
| Vapor Density | 3.66 |
| Specific Gravity | 0.864 |
| Solubility | slightly soluble |
| Partition coefficient; n-octanol/water | No data available |
| Autoignition Temperature | 465 °C / 869 °F |
| Decomposition Temperature | No information available |
| Viscosity | 0.62 mPa.s at 20 °C |
| Molecular Formula | C8 H10 |
| Molecular Weight | 106.17 |

10. Stability and reactivity

Reactive Hazard

None known, based on information available

| | |
|---|---|
| Stability | Stable under normal conditions. |
| Conditions to Avoid | Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition. |
| Incompatible Materials | Strong oxidizing agents, Strong acids |
| Hazardous Decomposition Products | Carbon monoxide (CO), Carbon dioxide (CO ₂) |
| Hazardous Polymerization | Hazardous polymerization does not occur. |
| Hazardous Reactions | None under normal processing. |

11. Toxicological information

Acute Toxicity

Product Information Component Information

| Component | LD50 Oral | LD50 Dermal | LC50 Inhalation |
|-----------|-----------------------|---|-----------------|
| m-Xylene | LD50 = 5 g/kg (Rat) | LD50 = 12.18 g/kg (Rabbit) LD50 = 14100 µL/kg (Rabbit) | Not listed |

Toxicologically Synergistic Products No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Irritating to eyes and skin

Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

| Component | CAS-No | IARC | NTP | ACGIH | OSHA | Mexico |
|-----------|----------|------------|------------|------------|------------|------------|
| m-Xylene | 108-38-3 | Not listed | Not listed | Not listed | Not listed | Not listed |

Mutagenic Effects No information available

Reproductive Effects No information available.

Developmental Effects No information available.

Teratogenicity No information available.

STOT - single exposure None known

STOT - repeated exposure None known

Aspiration hazard No information available

Symptoms / effects, both acute and delayed Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

The product contains following substances which are hazardous for the environment. Contains a substance which is: Toxic to aquatic organisms.

| Component | Freshwater Algae | Freshwater Fish | Microtox | Water Flea |
|-----------|--|---|-------------------------|---|
| m-Xylene | EC50: = 4.9 mg/L, 72h static (Pseudokirchneriella subcapitata) | LC50: = 8.4 mg/L, 96h semi-static (Oncorhynchus mykiss) LC50: 14.3 - 18 mg/L, 96h flow-through (Pimephales promelas) LC50: = 12.9 mg/L, 96h semi-static (Poecilia reticulata) | EC50 = 0.0084 mg/L 24 h | EC50: 2.81 - 5.0 mg/L, 48h Static (Daphnia magna) |

Persistence and Degradability Persistence is unlikely

Bioaccumulation/ Accumulation No information available.

Mobility Will likely be mobile in the environment due to its volatility. Is not likely mobile in the environment due its low water solubility.

| Component | log Pow |
|-----------|---------|
| m-Xylene | 3.2 |

13. Disposal considerations

Waste Disposal Methods Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

14. Transport information

DOT

UN-No UN1307
 Proper Shipping Name XYLENES
 Hazard Class 3
 Packing Group III

TDG

UN-No UN1307
 Proper Shipping Name XYLENES
 Hazard Class 3
 Packing Group III

IATA

UN-No UN1307
 Proper Shipping Name XYLENES
 Hazard Class 3
 Packing Group III

IMDG/IMO

UN-No UN1307
 Proper Shipping Name XYLENES
 Hazard Class 3
 Packing Group III

15. Regulatory information

All of the components in the product are on the following Inventory lists: X = listed

International Inventories

| Component | TSCA | DSL | NDSL | EINECS | ELINCS | NLP | PICCS | ENCS | AICS | IECSC | KECL |
|-----------|------|-----|------|-----------|--------|-----|-------|------|------|-------|------|
| m-Xylene | X | X | - | 203-576-3 | - | | X | X | X | X | X |

Legend:

X - Listed

E - Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.

F - Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.

N - Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated

polymer made with any free-radical initiator regardless of the amount used.

P - Indicates a commenced PMN substance

R - Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.

S - Indicates a substance that is identified in a proposed or final Significant New Use Rule

T - Indicates a substance that is the subject of a Section 4 test rule under TSCA.

XU - Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B)).

Y1 - Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.

Y2 - Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

U.S. Federal Regulations

TSCA 12(b) Not applicable

SARA 313

| Component | CAS-No | Weight % | SARA 313 - Threshold Values % |
|-----------|----------|----------|-------------------------------|
| m-Xylene | 108-38-3 | >95 | 1.0 |

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act)

| Component | CWA - Hazardous Substances | CWA - Reportable Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants |
|-----------|----------------------------|-----------------------------|------------------------|---------------------------|
| m-Xylene | X | - | - | - |

Clean Air Act

| Component | HAPS Data | Class 1 Ozone Depletors | Class 2 Ozone Depletors |
|-----------|-----------|-------------------------|-------------------------|
| m-Xylene | X | | - |

OSHA Occupational Safety and Health Administration

Not applicable

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

| Component | Hazardous Substances RQs | CERCLA EHS RQs |
|-----------|--------------------------|----------------|
| m-Xylene | 1000 lb | - |

California Proposition 65 This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

| Component | Massachusetts | New Jersey | Pennsylvania | Illinois | Rhode Island |
|-----------|---------------|------------|--------------|----------|--------------|
| m-Xylene | X | X | X | X | - |

U.S. Department of Transportation

Reportable Quantity (RQ): N
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade No information available

16. Other information

| | |
|-------------------------|---|
| Prepared By | Regulatory Affairs Thermo Fisher Scientific Email: EMSDS.RA@thermofisher.com |
| Creation Date | 26-Sep-2009 |
| Revision Date | 23-Jan-2018 |
| Print Date | 23-Jan-2018 |
| Revision Summary | This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS). |

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS