

COMPANY IDENTITY: Packaging Service Co., Inc.
 PRODUCT IDENTITY: CROWN PAINT THINNER
 SDS NUMBER: PT

SDS DATE: 02/05/2014
 REPLACES: 06/06/2011

SAFETY DATA SHEET

This Safety Data Sheet conforms to ANSI Z400.5, and to the format requirements and the International Chemical Safety Cards of the Global Harmonizing System.

THIS SDS COMPLIES WITH 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD)

IMPORTANT: Read this SDS before handling & disposing of this product.

Pass this information on to employees, customers, & users of this product.

SECTION 1. IDENTIFICATION OF THE SUBSTANCE OR MIXTURE AND OF THE SUPPLIER

PRODUCT IDENTITY: CROWN PAINT THINNER
 PRODUCT USES: Paint Thinner

COMPANY IDENTITY: Packaging Service Co., Inc.
 COMPANY ADDRESS: 1904 Mykawa Road
 COMPANY CITY: Pearland, TX 77581
 COMPANY PHONE: 1-281-485-1458
 EMERGENCY PHONES: CHEMTREC: 1-800-424-9300 (USA)
 CANUTEC: 1-613-996-6666 (CANADA)



SECTION 2. HAZARDS IDENTIFICATION

DANGER!!

EXPOSURE PREVENTION: PREVENT DISPERSION OF MISTS OR DUST!

2.1 HAZARD STATEMENTS: (CAT = Hazard Category)

H100s = General, H200s = Physical, H300s = Health, H400s = Environmental
 H226 Combustible liquid(N.America);Flammable liquid & vapor(Elsewhere).(CAT:3)
 H304 May be fatal if swallowed and enters airways.
 H315 Causes skin irritation.(CAT:2)
 H320 Causes eye irritation.(CAT:2)
 H332 Harmful if inhaled.(CAT:4)
 H335 May cause respiratory irritation.(CAT:3)
 H371 May cause damage to organs.(CAT:2)

2.2 PRECAUTIONARY STATEMENTS:

P100s = General, P200s = Prevention, P300s = Response, P400s = Storage, P500s = Disposal
 P260 Do not breathe dust/fume/gas/mist/vapors/spray.
 P264 Wash with soap & water thoroughly after handling.
 P270 Do not eat, drink or smoke when using this product.
 P271 Use only outdoors or in a well-ventilated area.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P302+352 IF ON SKIN: Wash with soap & water.
 P304+340 IF INHALED: Remove victim to fresh air & keep at rest in a position comfortable for breathing.
 P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present & easy to do - Continue rinsing.
 P309+311 If exposed or you feel unwell: Call a POISON CENTER or doctor/physician.
 P332+313 If skin irritation occurs: Get medical advice/attention.
 P337+313 If eye irritation persists, get medical advice/attention.
 P361 Remove/Take off immediately all contaminated clothing.
 P363 Wash contaminated clothing before reuse.
 P405 Store locked up.
 P501 Dispose of contents/container to appropriate waste site or reclaimer in accordance with local and national regulations.

SEE SECTIONS 8, 11 & 12 FOR TOXICOLOGICAL INFORMATION.

COMPANY IDENTITY: Packaging Service Co., Inc.
PRODUCT IDENTITY: CROWN PAINT THINNER
SDS NUMBER: PT

SDS DATE: 02/05/2014
REPLACES: 06/06/2011

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

MATERIAL	CAS#	EINECS#	WT %
Medium Aliphatic Naphtha	*64742-88-7	-	90-100
1,2,4-Trimethylbenzene	95-63-6	202-436-9	0- 5

TRACE COMPONENTS: Trace ingredients (if any) are present in < 1% concentration, (< 0.1% for potential carcinogens, reproductive toxins, respiratory tract mutagens, and sensitizers). None of the trace ingredients contribute significant additional hazards at the concentrations that may be present in this product. All pertinent hazard information has been provided in this document, per the requirements of the Federal Occupational Safety and Health Administration Standard (29 CFR 1910.1200), U.S. State equivalents, and Canadian Hazardous Materials Identification System Standard (CPR 4).

SECTION 4. FIRST AID MEASURES

4.1 GENERAL ADVICE:

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists, refer to Section 8 for specific personal protective equipment.

4.2 EYE CONTACT:

If this product enters the eyes, open eyes while under gently running water. Use sufficient force to open eyelids. "Roll" eyes to expose more surface. Minimum flushing is for 15 minutes. Seek immediate medical attention.

4.3 SKIN CONTACT:

If the product contaminates the skin, immediately begin decontamination with running water. Minimum flushing is for 15 minutes. Remove contaminated clothing, taking care not to contaminate eyes. If skin becomes irritated and irritation persists, medical attention may be necessary. Wash contaminated clothing before reuse, discard contaminated shoes.

4.4 INHALATION:

After high vapor exposure, remove to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, trained personnel should immediately begin artificial respiration. If the heart has stopped, trained personnel should immediately begin cardiopulmonary resuscitation (CPR). Seek immediate medical attention.

4.5 SWALLOWING:

If swallowed, CALL PHYSICIAN OR POISON CONTROL CENTER FOR MOST CURRENT INFORMATION. If professional advice is not available, give two glasses of water to drink. DO NOT INDUCE VOMITING. Never induce vomiting or give liquids to someone who is unconscious, having convulsions, or unable to swallow. Seek immediate medical attention.

4.6 NOTES TO PHYSICIAN:

There is no specific antidote. Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient. Any material aspirated during vomiting may cause lung injury. Therefore, emesis should not be induced mechanically or pharmacologically. If it is considered necessary to evacuate the stomach contents, this should be done by means least likely to cause aspiration (such as: Gastric lavage after endotracheal intubation).

SECTION 5. FIRE FIGHTING MEASURES

5.1 FIRE & EXPLOSION PREVENTIVE MEASURES

NO open flames, NO sparks, & NO smoking. Above flash point, use a closed system, ventilation, explosion-proof electrical equipment, lighting.

COMPANY IDENTITY: Packaging Service Co., Inc.
PRODUCT IDENTITY: CROWN PAINT THINNER
SDS NUMBER: PT

SDS DATE: 02/05/2014
REPLACES: 06/06/2011

SECTION 5. FIRE FIGHTING MEASURES (CONTINUED)

5.2 EXTINGUISHING MEDIA

Use dry powder, AFFF, alcohol-resistant foam, water spray, carbon dioxide.

5.3 SPECIAL FIRE FIGHTING PROCEDURES

Water spray may be ineffective on fire but can protect fire-fighters & cool closed containers. Use fog nozzles if water is used. Do not enter confined fire-space without full bunker gear. (Helmet with face shield, bunker coats, gloves & rubber boots).

5.4 UNUSUAL EXPLOSION AND FIRE PROCEDURES

COMBUSTIBLE!

Isolate from oxidizers, heat, & open flame.
Closed containers may explode if exposed to extreme heat.
Applying to hot surfaces requires special precautions.
Empty container very hazardous! Continue all label precautions!

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1 SPILL AND LEAK RESPONSE AND ENVIRONMENTAL PRECAUTIONS:

Uncontrolled releases should be responded to by trained personnel using pre-planned procedures. Proper protective equipment should be used. In case of a spill, clear the affected area, protect people, and respond with trained personnel. Extinguish or turn off all ignition sources. Ventilate the involved space.

6.2 PERSONAL PROTECTIVE EQUIPMENT

The proper personal protective equipment for incidental releases (such as: 1 Liter of the product released in a well-ventilated area), use impermeable gloves, they should be Level B: **triple-gloves (rubber gloves and nitrile gloves over latex gloves), chemical resistant suit and boots, hard-hat, and Self-Contained Breathing Apparatus** specific for the material handled, goggles, face shield, and appropriate body protection. In the event of a large release, use impermeable gloves, specific for the material handled, chemically resistant suit and boots, and hard hat. Self-Contained Breathing Apparatus or respirator may be required where engineering controls are not adequate or conditions for potential exposure exist. When respirators are required, select NIOSH/MSHA approved based on actual or potential airborne concentrations in accordance with latest OSHA and/or ANSI recommendations.

6.3 ENVIRONMENTAL PRECAUTIONS:

Stop spill at source. Construct temporary dikes of dirt, sand, or any appropriate readily available material to prevent spreading of the material. Close or cap valves and/or block or plug hole in leaking container and transfer to another container. Keep from entering storm sewers and ditches which lead to waterways, and if necessary, call the local fire or police department for immediate emergency assistance.

6.4 CONTAINMENT AND CLEAN-UP MEASURES:

Absorb spilled liquid with polypads or other suitable absorbent materials. If necessary, neutralize using suitable buffering material, (acid with soda ash or base with phosphoric acid), and test area with litmus paper to confirm neutralization. Clean up with non-combustible absorbent (such as: sand, soil, and so on). Shovel up and place all spill residue in suitable containers. dispose of at an appropriate waste disposal facility according to current applicable laws and regulations and product characteristics at time of disposal (see Section 13 - Disposal Considerations).

COMPANY IDENTITY: Packaging Service Co., Inc.
PRODUCT IDENTITY: CROWN PAINT THINNER
SDS NUMBER: PT

SDS DATE: 02/05/2014
REPLACES: 06/06/2011

SECTION 7. HANDLING AND STORAGE

7.1 HANDLING

Isolate from oxidizers, heat, & open flame. Use only with adequate ventilation. Avoid breathing of vapor or spray mist. Avoid contact with skin & eyes. Wear OSHA Standard goggles or face shield. Consult Safety Equipment Supplier. Wear goggles, face shield, gloves, apron & footwear impervious to material. Wash clothing before reuse.

Avoid free fall of liquid. Ground containers when transferring. Do not flame cut, braze, or weld. Empty container very hazardous! Continue all label precautions!

7.2 STORAGE

Keep in fireproof surroundings. Keep separated from strong oxidants.

Keep container tightly closed & upright when not in use to prevent leakage.

Store containers in a cool, dry location, away from direct sunlight, sources of intense heat, or where freezing is possible. Store containers away from incompatible materials.

Inspect all incoming containers before storage to ensure containers are properly labeled and not damaged.

7.3 NONBULK: CONTAINERS:

Store containers in a cool, dry location, away from direct sunlight, sources of intense heat, or where freezing is possible. Material should be stored in secondary containers or in a diked area, as appropriate. Store containers away from incompatible chemicals (see Section 10, Stability and Reactivity). Post warning and "NO SMOKING" signs in storage and use areas, as appropriate. Empty containers should be handled with care. Never store food, feed, or drinking water in containers which held this product.

7.4 BULK CONTAINERS:

All tanks and pipelines which contain this material must be labeled. Perform routine maintenance on tanks or pipelines which contain this product. Report all leaks immediately to the proper personnel.

7.5 TANK CAR SHIPMENTS:

Tank cars carrying this product should be loaded and unloaded in strict accordance with tank-car manufacturer's recommendation and all established on-site safety procedures. Appropriate personal protective equipment must be used (see Section 8, Engineering Controls and Personal Protective Equipment.). All loading and unloading equipment must be inspected, prior to each use. Loading and unloading operations must be attended, at all times. Tank cars must be level, brakes must be set or wheels must be locked or blocked prior to loading or unloading. Tank car (for loading) or storage tanks (for unloading) must be verified to be correct for receiving this product and be properly prepared, prior to starting the transfer operations. Hoses must be verified to be in the correct positions, before starting transfer operations. A sample (if required) must be taken and verified (if required) prior to starting transfer operations. All lines must be blown-down and purged before disconnecting them from the tank car or vessel.

7.6 PROTECTIVE PRACTICES DURING MAINTENANCE OF CONTAMINATED EQUIPMENT:

Follow practices indicated in Section 6 (Accidental Release Measures). Make certain application equipment is locked and tagged-out safely. Always use this product in areas where adequate ventilation is provided. Collect all rinsates and dispose of according to applicable Federal, State, Provincial, or local procedures.

7.7 EMPTY CONTAINER WARNING:

Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. **DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY BURST AND CAUSE INJURY OR DEATH.**

COMPANY IDENTITY: Packaging Service Co., Inc.
 PRODUCT IDENTITY: CROWN PAINT THINNER
 SDS NUMBER: PT

SDS DATE: 02/05/2014
 REPLACES: 06/06/2011

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

MATERIAL	CAS#	EINECS#	TWA (OSHA)	TLV (ACGIH)
Medium Aliphatic Naphtha	*64742-88-7	-	500 ppm	100 ppm
1,2,4-Trimethylbenzene	95-63-6	202-436-9	25 ppm	25 ppm

This product contains no EPA Hazardous Air Pollutants (HAP) in amounts > 0.1%.
 EPA Hazardous Air Pollutants may be present in trace amounts (less than 0.1%):
 Polycyclic Aromatics

8.1 RESPIRATORY EXPOSURE CONTROLS

Maintain airborne contaminant concentrations below exposure limits given above. If respiratory protection is needed, use only protection authorized in 29 CFR 1910.134, European Standard EN 149, or applicable State regulations. If adequate ventilation is not available or there is potential for airborne exposure above the exposure limits, a respirator may be worn up to the respirator exposure limitations, check with respirator equipment manufacturer's recommendations/limitations. For a higher level of protection, use positive pressure supplied air respiration protection or Self-Contained Breathing Apparatus or if oxygen levels are below 19.5% or are unknown.

8.2 EMERGENCY OR PLANNED ENTRY INTO UNKNOWN CONCENTRATIONS OR IDLH CONDITIONS

Positive pressure, full-face piece Self-Contained Breathing Apparatus; or positive pressure, full-face piece Self-Contained Breathing Apparatus with an auxilliary positive pressure Self-Contained Breathing Apparatus.

8.3 VENTILATION

LOCAL EXHAUST: Necessary MECHANICAL (GENERAL): Necessary
 SPECIAL: None OTHER: None
 Please refer to ACGIH document, "Industrial Ventilation, A Manual of Recommended Practices", most recent edition, for details.

8.4 EYE PROTECTION:

Splash goggles or safety glasses. Face-shields are recommended when the operation can generate splashes, sprays or mists.

8.5 HAND PROTECTION:

Use gloves chemically resistant to this material. Preferred examples: Butyl rubber, Chlorinated Polyethylene, Polyethylene, Ethyl Vinyl Alcohol Laminate ("EVAL"), Polyvinyl Alcohol ("PVA"). Examples of acceptable glove barrier materials include: Natural Rubber ("Latex"), Neoprene, Nitrile/Butadiene Rubber ("Nitril") or ("NBR"), Polyvinyl Chloride ("PVC" or "Vinyl"), Viton. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

8.6 BODY PROTECTION:

Use body protection appropriate for task. Cover-all, rubber aprons, or chemical protective clothing made from impervious materials are generally acceptable, depending on the task.

8.7 WORK & HYGIENIC PRACTICES:

Provide readily accessible eye wash stations & safety showers. Wash at end of each shift & before eating, smoking or using the toilet. Remove clothing that becomes contaminated. Destroy contaminated leather articles. Launder or discard contaminated clothing.

COMPANY IDENTITY: Packaging Service Co., Inc.
 PRODUCT IDENTITY: CROWN PAINT THINNER
 SDS NUMBER: PT

SDS DATE: 02/05/2014
 REPLACES: 06/06/2011

SECTION 9. PHYSICAL & CHEMICAL PROPERTIES

APPEARANCE:	Liquid, Water-White
ODOR:	Mild
ODOR THRESHOLD:	Not Available
pH (Neutrality):	Not Available
MELTING POINT/FREEZING POINT:	Not Available
BOILING RANGE (IBP,50%,Dry Point):	161 176 197* C / 323 350 388* F (*=End Point)
FLASH POINT (TEST METHOD):	45 C / 114 F (TCC)
EVAPORATION RATE (n-Butyl Acetate=1):	0.214
FLAMMABILITY CLASSIFICATION:	Class II
LOWER FLAMMABLE LIMIT IN AIR (% by vol):	0.95
UPPER FLAMMABLE LIMIT IN AIR (% by vol):	Not Available
VAPOR PRESSURE (mm of Hg)@20 C	1.0
VAPOR DENSITY (air=1):	4.9
GRAVITY @ 68/68 F / 20/20 C:	
DENSITY:	0.783
SPECIFIC GRAVITY (Water=1):	0.784
POUNDS/GALLON:	6.531
WATER SOLUBILITY:	Negligible
PARTITION COEFFICIENT (n-Octane/Water):	Not Available
AUTO IGNITION TEMPERATURE:	276 C / 530 F
DECOMPOSITION TEMPERATURE:	Not Available
REFRACTIVE INDEX:	1.437
VOCs (>0.044 Lbs/Sq In) :	98.0 Vol% / 768.3 g/L / 6.4 Lbs/Gal
TOTAL VOC'S (TVOC)*:	98.0 Vol% / 768.3 g/L / 6.4 Lbs/Gal
NONEXEMPT VOC'S (CVOC)*:	98.0 Vol% / 768.3 g/L / 6.4 Lbs/Gal
HAZARDOUS AIR POLLUTANTS (HAPS):	0.0 Wt% / 25.0 g/L / .2 Lbs/Gal
NONEXEMPT VOC PARTIAL PRESSURE (mm of Hg @ 20 C)	0.0
VISCOSITY @ 20 C (ASTM D445):	Not Available

* Using CARB (California Air Resources Board Rules).

SECTION 10. STABILITY & REACTIVITY

10.1 STABILITY

Stable under normal conditions.

10.2 CONDITIONS TO AVOID

Isolate from oxidizers, heat, & open flame.

10.3 MATERIALS TO AVOID

Reacts with strong oxidants, causing fire & explosion hazard. Attacks many plastics, rubber.

10.4 HAZARDOUS DECOMPOSITION PRODUCTS

Carbon Monoxide, Carbon Dioxide from burning.

10.5 HAZARDOUS POLYMERIZATION

Will not occur.

COMPANY IDENTITY: Packaging Service Co., Inc.
PRODUCT IDENTITY: CROWN PAINT THINNER
SDS NUMBER: PT

SDS DATE: 02/05/2014
REPLACES: 06/06/2011

SECTION 11. TOXICOLOGICAL INFORMATION

11.1 ACUTE HAZARDS

11.11 EYE & SKIN CONTACT:

Primary irritation to skin, defatting, dermatitis.
Primary irritation to eyes, redness, tearing, blurred vision.
Liquid can cause eye irritation. Wash thoroughly after handling.

11.12 INHALATION:

Anesthetic. Irritates respiratory tract. Acute overexposure can cause serious nervous system depression. Vapor harmful.

11.13 SWALLOWING:

Harmful or fatal if swallowed.
Swallowing can cause abdominal irritation, nausea, vomiting & diarrhea.
The symptoms of chemical pneumonitis may not show up for a few days.

11.2 SUBCHRONIC HAZARDS/CONDITIONS AGGRAVATED

CONDITIONS AGGRAVATED

Persons with severe skin, liver or kidney problems should avoid use.

11.3 CHRONIC HAZARDS

11.31 CANCER, REPRODUCTIVE & OTHER CHRONIC HAZARDS:

Lung tumors have been reported in laboratory mice.
Leukemia been reported in humans from Benzene.
This product contains less than 1 ppm of Benzene.
Not considered hazardous in such low concentrations.
Absorption thru skin may be harmful.

IRRITANCY OF PRODUCT: This product is irritating to contaminated tissue.

SENSITIZATION TO THE PRODUCT: No component of this product is known to be a sensitizer.

MUTAGENICITY: This product is not reported to produce mutagenic effects in humans.

EMBRYOTOXICITY: This product is not reported to produce embryotoxic effects in humans.

TERATOGENICITY: This product is not reported to produce teratogenic effects in humans.

REPRODUCTIVE TOXICITY: This product is not reported to cause reproductive effects in humans.

A mutagen is a chemical which causes permanent changes to genetic material (DNA) such that the changes will propagate through generational lines. An embryotoxin is a chemical which causes damage to a developing embryo (such as: within the eight weeks of pregnancy in humans), but the damage does not propagate across generational lines. A teratogen is a chemical which causes damage to a developing fetus, but the damage does not propagate across generational lines. A reproductive toxin is any substance which interferes in any way with the reproductive process.

11.4 MAMMALIAN TOXICITY INFORMATION

No mammalian information is available on this product.

COMPANY IDENTITY: Packaging Service Co., Inc.
PRODUCT IDENTITY: CROWN PAINT THINNER
SDS NUMBER: PT

SDS DATE: 02/05/2014
REPLACES: 06/06/2011

SECTION 12. ECOLOGICAL INFORMATION

12.1 ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

12.2 EFFECT OF MATERIAL ON PLANTS AND ANIMALS:

This product may be harmful or fatal to plant and animal life if released into the environment. Refer to Section 11 (Toxicological Information) for further data on the effects of this product's components on test animals.

12.3 EFFECT OF MATERIAL ON AQUATIC LIFE:

The most sensitive known aquatic group to any component of this product is: Fish are adversely affected by components of this product. Environmental effects of the substance have not been investigated adequately.

12.4 MOBILITY IN SOIL

This material is a mobile liquid.

12.5 DEGRADABILITY

This product is nonbiodegradable.

12.6 ACCUMULATION

This product does not accumulate or biomagnify in the environment.

SECTION 13. DISPOSAL CONSIDERATIONS

The generation of waste should be avoided or minimized wherever possible. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers and liners may retain some product residues. Vapor from some product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Processing, use or contamination may change the waste disposal requirements. Do not dispose of on land, in surface waters, or in storm drains. Waste should be recycled or disposed of in accordance with regulations. Large amounts should be collected for reuse or consigned to licensed hazardous waste haulers for disposal. **ALL DISPOSAL MUST BE IN ACCORDANCE WITH ALL FEDERAL, STATE, PROVINCIAL, AND LOCAL REGULATIONS. IF IN DOUBT, CONTACT PROPER AGENCIES. EPA CHARACTERISTIC: D001**

SECTION 14. TRANSPORT INFORMATION

MARINE POLLUTANT: No
DOT/TDG SHIP NAME: BULK: UN1263, Paint Related Material, Combustible liquid, PG-III
Combustible liquid. Not DOT regulated on trucks in containers of < 119 gallons.
DRUM LABEL: None (Combustible Liquid)
IATA / ICAO: UN1263, Paint Related Material, 3, PG-III
IMO / IMDG: UN1263, Paint Related Material, 3, PG-III
EMERGENCY RESPONSE GUIDEBOOK NUMBER: 128



COMPANY IDENTITY: Packaging Service Co., Inc.
PRODUCT IDENTITY: CROWN PAINT THINNER
SDS NUMBER: PT

SDS DATE: 02/05/2014
REPLACES: 06/06/2011

SECTION 15. REGULATORY INFORMATION

15.1 EPA REGULATION:

SARA SECTION 311/312 HAZARDS: Acute Health, Fire

All components of this product are on the TSCA list.
This material contains no known products restricted under SARA Title III,
Section 313 in amounts greater or equal to 1%.

15.2 STATE REGULATIONS:

CALIFORNIA SAFE DRINKING WATER & TOXIC ENFORCEMENT ACT (PROPOSITION 65):
This product contains no chemicals known to the State of California
to cause cancer or reproductive toxicity.

15.3 INTERNATIONAL REGULATIONS

The identified components of this product are listed on the chemical inventories
of the following countries:
Australia (AICS), Canada (DSL or NDSL), China (IECSC), Europe (EINECS, ELINCS),
Japan (METI/CSCL, MHLW/ISHL), South Korea (KECI), New Zealand (NZIoC),
Philippines (PICCS), Switzerland (SWISS), Taiwan (NECSI), USA (TSCA).

15.4 CANADA: WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (WHMIS)

B3: Combustible Liquid.
D2B: Irritating to skin / eyes.

This product has been classified in accordance with hazard criteria of the Controlled
Products Regulations (CPR) and the SDS contains all information required by the CPR.

SECTION 16. OTHER INFORMATION

16.1 HAZARD RATINGS:

HEALTH (NFPA): 1, HEALTH (HMIS): 1, FLAMMABILITY: 2, PHYSICAL HAZARD: 0
(Personal Protection Rating to be supplied by user based on use conditions.)
This information is intended solely for the use of individuals
trained in the NFPA & HMIS hazard rating systems.

16.2 EMPLOYEE TRAINING

See Section 2 for Risk & Safety Statements. Employees should be made aware
of all hazards of this material (as stated in this SDS) before handling it.

16.3 SDS DATE: 02/05/2014

NOTICE

The supplier disclaims all expressed or implied warranties of merchantability or fitness
for a specific use, with respect to the product or the information provided herein,
except for conformation to contracted specifications. All information appearing herein
is based upon data obtained from manufacturers and/or recognized technical sources.
While the information is believed to be accurate, we make no representations as to its
accuracy or sufficiency.
Conditions of use are beyond our control, and therefore users are responsible for
verifying the data under their own operating conditions to determine whether the product
is suitable for their particular purposes and they assume all risks of their handling,
and disposal of the product. Users also assume all risks in regards to the publication
or use of, or reliance upon information contained herein.
This information relates only to the product designated herein, and does not relate to
its use in combination with any other material or process.

Unless updated, the Safety Data Sheet is valid until 02/05/2017.