

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 30, 2019

1 Identification

- **Product identifier**
- **Trade name:** ASA-WFTC SPRAY INSULATION ADHESIVE
- **Product code:** 5163
- **Recommended use and restriction on use**
- **Recommended use:** Adhesives
- **Restrictions on use:** No relevant information available.
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
DURO DYNE CORPORATION
81 Spence Street
Bay Shore, NY 11706
800-899-3876
- **Emergency telephone number:**
ChemTel Inc.
(800)255-3924 (North America)
+1 (813)248-0585 (International)

2 Hazard(s) identification

- **Classification of the substance or mixture**
Flam. Aerosol 1 H222 Extremely flammable aerosol.
Press. Gas H280 Contains gas under pressure; may explode if heated.
Eye Irrit. 2A H319 Causes serious eye irritation.
Repr. 2 H361 Suspected of damaging fertility or the unborn child.
STOT SE 3 H336 May cause drowsiness or dizziness.
STOT RE 2 H373 May cause damage to the gastro-intestinal tract through prolonged or repeated exposure. Route of exposure: Inhalation.
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms:**



GHS02 GHS04 GHS07 GHS08

- **Signal word:** Danger

- **Hazard statements:**

H222 Extremely flammable aerosol.
H280 Contains gas under pressure; may explode if heated.
H319 Causes serious eye irritation.
H361 Suspected of damaging fertility or the unborn child.
H336 May cause drowsiness or dizziness.
H373 May cause damage to the gastro-intestinal tract through prolonged or repeated exposure. Route of exposure: Inhalation.

(Cont'd. on page 2)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 30, 2019

Trade name: ASA-WFTC SPRAY INSULATION ADHESIVE

(Cont'd. of page 1)

H304 May be fatal if swallowed and enters airways.

Precautionary statements:

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Pressurized container: Do not pierce or burn, even after use.
- P260 Do not breathe mist/vapors/spray.
- P264 Wash thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection.
- P301+P310 If swallowed: Immediately call a poison center/doctor.
- P331 Do NOT induce vomiting.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P312 Call a poison center/doctor if you feel unwell.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P405 Store locked up.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Components:

74-98-6	Propane  Flam. Gas 1, H220  Press. Gas, H280 Simple Asphyxiant	20-<50%
67-64-1	Acetone  Flam. Liq. 2, H225  Eye Irrit. 2A, H319; STOT SE 3, H336	20-<50%
64742-49-0	Naphtha (petroleum), hydrotreated light (Nota P, <0.1% benzene)  Flam. Liq. 2, H225  Asp. Tox. 1, H304	10-<25%
115-10-6	dimethyl ether  Flam. Gas 1, H220  Press. Gas, H280	3-7%
142-82-5	Heptane  Flam. Liq. 2, H225  Asp. Tox. 1, H304  Skin Irrit. 2, H315; STOT SE 3, H336	1-<5%
64742-52-5	Distillates (petroleum), hydrotreated heavy naphthenic	1-<5%

(Cont'd. on page 3)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 30, 2019

Trade name: ASA-WFTC SPRAY INSULATION ADHESIVE

(Cont'd. of page 2)

	 Asp. Tox. 1, H304	
110-54-3	n-hexane  Flam. Liq. 2, H225  Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304  Skin Irrit. 2, H315; STOT SE 3, H336  Eye Irrit. 2B, H320	1-<3%
108-87-2	methylcyclohexane  Flam. Liq. 2, H225  Asp. Tox. 1, H304  Skin Irrit. 2, H315; STOT SE 3, H336	0.1-<1%

Additional information:

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret.
For the wording of the listed Hazard Statements, refer to section 16.

4 First-aid measures

Description of first aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation is experienced, consult a doctor.

After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

Most important symptoms and effects, both acute and delayed:

Dizziness

Coughing

Causes eye irritation.

Slight irritant effect on skin and mucous membranes.

Disorientation

Danger:

May cause damage to the gastro-intestinal tract through prolonged or repeated exposure. Route of exposure: Inhalation.

Suspected of damaging fertility or the unborn child.

Indication of any immediate medical attention and special treatment needed: Treat symptomatically.

5 Fire-fighting measures

Extinguishing media

Suitable extinguishing agents:

Gaseous extinguishing agents

Carbon dioxide

Water fog / haze

Fire-extinguishing powder

Foam

(Cont'd. on page 4)



Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 30, 2019

Trade name: ASA-WFTC SPRAY INSULATION ADHESIVE

(Cont'd. of page 3)

- **For safety reasons unsuitable extinguishing agents:** Water stream.
- **Special hazards arising from the substance or mixture**
Extremely flammable aerosol.
Danger of receptacles bursting because of high vapor pressure if heated.
- **Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.
- **Additional information:**
Eliminate all ignition sources if safe to do so.
Use large quantities of foam as it is partially destroyed by the product.
Cool endangered product with water spray.
Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation.
Keep away from ignition sources.
Use respiratory protective device against the effects of fumes/dust/aerosol.
Protect from heat.
- **Environmental precautions**
Do not allow to enter sewers/ surface or ground water.
Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up**
Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).
Allow to solidify. Pick up mechanically.
Send for recovery or disposal in suitable receptacles.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling**
- **Precautions for safe handling:**
Use only in well ventilated areas.
Keep away from heat and direct sunlight.
Avoid contact with the eyes and skin.
Avoid breathing mist, vapors, or spray.
Open and handle receptacle with care.
- **Information about protection against explosions and fires:**
Danger of receptacles bursting because of high vapor pressure if heated.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Do not spray on a naked flame or any incandescent material.

(Cont'd. on page 5)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 30, 2019

Trade name: ASA-WFTC SPRAY INSULATION ADHESIVE

(Cont'd. of page 4)

Emergency cooling must be available in case of nearby fire.

- **Conditions for safe storage, including any incompatibilities**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:**
Store away from foodstuffs.
Store away from oxidizing agents.
- **Further information about storage conditions:**
Store in a cool place. Heat will increase pressure and may lead to the container bursting.
- **Specific end use(s)** No relevant information available.

8 Exposure controls/personal protection

· Control parameters

· Components with limit values that require monitoring at the workplace:

74-98-6 Propane

PEL (USA)	Long-term value: 1800 mg/m ³ , 1000 ppm
REL (USA)	Long-term value: 1800 mg/m ³ , 1000 ppm
TLV (USA)	refer to Appendix F in TLVs&BEIs book; D, EX
EL (Canada)	Simple asphyxiant; EX
EV (Canada)	Long-term value: 1,000 ppm revoked as of 01/01/18
LMPE (Mexico)	Long-term value: 1000 ppm

67-64-1 Acetone

PEL (USA)	Long-term value: 2400 mg/m ³ , 1000 ppm
REL (USA)	Long-term value: 590 mg/m ³ , 250 ppm
TLV (USA)	Short-term value: 1187 mg/m ³ , 500 ppm Long-term value: 594 mg/m ³ , 250 ppm BEI
EL (Canada)	Short-term value: 500 ppm Long-term value: 250 ppm
EV (Canada)	Short-term value: 750 ppm Long-term value: 500 ppm
LMPE (Mexico)	Short-term value: 750 ppm Long-term value: 500 ppm A4, IBE

115-10-6 dimethyl ether

WEEL (USA)	Long-term value: 1000 ppm
EL (Canada)	Long-term value: 1000 ppm

142-82-5 Heptane

PEL (USA)	Long-term value: 2000 mg/m ³ , 500 ppm
REL (USA)	Long-term value: 350 mg/m ³ , 85 ppm Ceiling limit value: 1800* mg/m ³ , 440* ppm *15-min

(Cont'd. on page 6)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 30, 2019

Trade name: ASA-WFTC SPRAY INSULATION ADHESIVE

(Cont'd. of page 5)

TLV (USA)	Short-term value: 2050 mg/m ³ , 500 ppm Long-term value: 1640 mg/m ³ , 400 ppm
EL (Canada)	Short-term value: 500 ppm Long-term value: 400 ppm
EV (Canada)	Short-term value: 2045 mg/m ³ , 500 ppm Long-term value: 1635 mg/m ³ , 400 ppm
LMPE (Mexico)	Short-term value: 500 ppm Long-term value: 400 ppm

110-54-3 n-hexane

PEL (USA)	Long-term value: 1800 mg/m ³ , 500 ppm
REL (USA)	Long-term value: 180 mg/m ³ , 50 ppm
TLV (USA)	Long-term value: 176 mg/m ³ , 50 ppm Skin; BEI
EL (Canada)	Long-term value: 20 ppm Skin
EV (Canada)	Long-term value: 176 mg/m ³ , 50 ppm
LMPE (Mexico)	Long-term value: 50 ppm PIEL, IBE

108-87-2 methylcyclohexane

PEL (USA)	Long-term value: 2000 mg/m ³ , 500 ppm
REL (USA)	Long-term value: 1600 mg/m ³ , 400 ppm
TLV (USA)	Long-term value: 1610 mg/m ³ , 400 ppm
EL (Canada)	Long-term value: 400 ppm
EV (Canada)	Long-term value: 1,600 mg/m ³ , 400 ppm
LMPE (Mexico)	Long-term value: 400 ppm

Ingredients with biological limit values:

67-64-1 Acetone

BEI (USA)	50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
-----------	--

110-54-3 n-hexane

BEI (USA)	0.4 mg/L Medium: urine Time: end of shift at end of workweek Parameter: 2,5-Hexanedione without hydrolysis
-----------	---

Exposure controls

General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.

• **Engineering controls:** Provide adequate ventilation.

• **Breathing equipment:** Suitable respiratory protective device recommended.

(Cont'd. on page 7)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 30, 2019

Trade name: ASA-WFTC SPRAY INSULATION ADHESIVE

(Cont'd. of page 6)

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Gloves should provide protection from freezing temperatures.

· **Eye protection:**



Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear.

· **Body protection:** Protective work clothing

· **Limitation and supervision of exposure into the environment**

No relevant information available.

· **Risk management measures** No relevant information available.

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **Appearance:**

Form:

Aerosol

Color:

According to product specification

· **Odor:**

Not determined.

· **Odor threshold:**

Not determined.

· **pH-value:**

Not determined.

· **Melting point/Melting range:**

Not determined.

· **Boiling point/Boiling range:**

40.69 °C (105.2 °F)

· **Flash point:**

-104.4 °C (-155.9 °F)

· **Flammability (solid, gaseous):**

Not applicable.

· **Auto-ignition temperature:**

Not determined.

· **Decomposition temperature:**

Not determined.

· **Danger of explosion:**

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits**

Lower:

1.5 Vol %

Upper:

7.5 Vol %

· **Oxidizing properties:**

Not determined.

· **Vapor pressure:**

5240 hPa (3930.3 mm Hg)

· **Density:**

Relative density:

<1

Vapor density:

Not determined.

Evaporation rate:

Not applicable.

(Cont'd. on page 8)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 30, 2019

Trade name: ASA-WFTC SPRAY INSULATION ADHESIVE

(Cont'd. of page 7)

- **Solubility in / Miscibility with Water:** Not miscible or difficult to mix.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity**
 - Dynamic:** Not determined.
 - Kinematic:** Not determined.
- **Other information** No relevant information available.

10 Stability and reactivity

- **Reactivity:** No relevant information available.
- **Chemical stability:** Stable under normal temperatures and pressures.
- **Thermal decomposition / conditions to be avoided:**
Danger of receptacles bursting because of high vapor pressure if heated.
- **Possibility of hazardous reactions**
Reacts violently with oxidizing agents.
Develops readily flammable gases / fumes.
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.
Extremely flammable aerosol.
Toxic fumes may be released if heated above the decomposition point.
- **Conditions to avoid** Excessive heat.
- **Incompatible materials** Oxidizers
- **Hazardous decomposition products**
Under fire conditions only:
Carbon monoxide and carbon dioxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:** Based on available data, the classification criteria are not met.
- **LD/LC50 values that are relevant for classification:** None.
- **Primary irritant effect:**
- **On the skin:** Irritant to skin and mucous membranes.
- **On the eye:** Causes eye irritation.
- **Sensitization:** Based on available data, the classification criteria are not met.
- **IARC (International Agency for Research on Cancer):**
Present in trace quantities.

71-43-2	Benzene	1
100-41-4	Ethylbenzene	2B
100-42-5	styrene	2B

- **NTP (National Toxicology Program):**
Present in trace quantities.

71-43-2	Benzene	K
100-42-5	styrene	R

(Cont'd. on page 9)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 30, 2019

Trade name: ASA-WFTC SPRAY INSULATION ADHESIVE

(Cont'd. of page 8)

· **OSHA-Ca (Occupational Safety & Health Administration):**

Present in trace quantities.

71-43-2	Benzene
---------	---------

· **Probable route(s) of exposure:**

Inhalation.

Eye contact.

Skin contact.

· **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.

· **Carcinogenicity:** Based on available data, the classification criteria are not met.

· **Reproductive toxicity:** Suspected of damaging fertility or the unborn child.

· **STOT-single exposure:** May cause drowsiness or dizziness.

· **STOT-repeated exposure:**

May cause damage to the gastro-intestinal tract through prolonged or repeated exposure. Route of exposure: Inhalation.

· **Aspiration hazard:** May be fatal if swallowed and enters airways.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity** Toxic to aquatic life with long lasting effects.

· **Persistence and degradability** No relevant information available.

· **Bioaccumulative potential:** No relevant information available.

· **Mobility in soil:** No relevant information available.

· **Additional ecological information**

· **General notes:** Avoid release to the environment.

· **Other adverse effects** No relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Contact waste processors for recycling information.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

· **Uncleaned packagings**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**

· **DOT, ADR/RID/ADN, IMDG, IATA**

UN1950

· **UN proper shipping name**

· **DOT**

Aerosols

(Cont'd. on page 10)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 30, 2019

Trade name: ASA-WFTC SPRAY INSULATION ADHESIVE

(Cont'd. of page 9)

· ADR/RID/ADN, IMDG

AEROSOLS

· IATA

Aerosols, flammable

· Transport hazard class(es)

· DOT



· Class

2.1

· Label

2.1

· ADR/RID/ADN



· Class

2.5F

· Label

2.1

· IMDG, IATA



· Class

2.1

· Label

2.1

· Packing group

Aerosols are not assigned a packing group.

· Environmental hazards

Product contains environmentally hazardous substances: Heptane, n-hexane

· Marine pollutant:



Yes

· Special precautions for user

Warning: Gases

· Danger code (Kemler):

-

· EMS Number:

F-D,S-U

· Segregation groups

Liquid halogenated hydrocarbons

· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

· Transport/Additional information:

· DOT



Limited Quantity for packages less than 30 kg gross and inner packagings less than 1 L.

(Cont'd. on page 11)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 30, 2019

Trade name: ASA-WFTC SPRAY INSULATION ADHESIVE

(Cont'd. of page 10)

· **ADR/RID/ADN**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 1 L.

· **IMDG**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 1 L.

· **IATA**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 1 L.

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **United States (USA)**

· **SARA**

· **Section 302 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

110-54-3 n-hexane

· **TSCA (Toxic Substances Control Act)**

All ingredients are listed or exempt.

· **Proposition 65 (California)**

· **Chemicals known to cause cancer:**

Present in trace quantities.

71-43-2 Benzene

100-41-4 Ethylbenzene

100-42-5 styrene

· **Chemicals known to cause developmental toxicity for females:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity for males:**

110-54-3 n-hexane

71-43-2 Benzene

· **Chemicals known to cause developmental toxicity:**

(Cont'd. on page 12)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 30, 2019

Trade name: ASA-WFTC SPRAY INSULATION ADHESIVE

(Cont'd. of page 11)

Present in trace quantities.

71-43-2	Benzene
108-88-3	Toluene

EPA (Environmental Protection Agency):

67-64-1	Acetone	I
142-82-5	Heptane	D
110-54-3	n-hexane	II

IARC (International Agency for Research on Cancer):

Present in trace quantities.

71-43-2	Benzene	1
100-41-4	Ethylbenzene	2B
100-42-5	styrene	2B

Canadian Domestic Substances List (DSL):

All ingredients are listed or exempt.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 OSHA: Occupational Safety & Health Administration
 Flam. Gas 1: Flammable gases – Category 1
 Flam. Aerosol 1: Aerosols – Category 1
 Press. Gas: Gases under pressure – Compressed gas
 Flam. Liq. 2: Flammable liquids – Category 2
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
 Eye Irrit. 2B: Serious eye damage/eye irritation – Category 2B
 Repr. 2: Reproductive toxicity – Category 2
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
 Asp. Tox. 1: Aspiration hazard – Category 1

Sources

Website, European Chemicals Agency (echa.europa.eu)
 Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/overview/home.do)
 Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)
 Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6
 Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaassen, Curtis D., ed., ISBN: 978-0-07-176923-5.
 Safety Data Sheets, Individual Manufacturers

SDS Prepared by:
 ChemTel Inc.

(Cont'd. on page 13)



Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: September 30, 2019

Trade name: ASA-WFTC SPRAY INSULATION ADHESIVE

(Cont'd. of page 12)

1305 North Florida Avenue
Tampa, Florida USA 33602-2902
Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573
Website: www.chemtelinc.com